XC Hybrid

XC Hybrid

Il programmatore XC a batteria offre controllo con o senza accesso alla corrente

Caratteristiche | **Modelli** | **Specifiche** | **Documenti**

Il programmatore XC Hybrid fornisce potenza ininterrotta. Avendo le stesse funzioni del programmatore XC, XC Hybrid opera però solo con solenoidi bistabili a 9 V e può essere alimentato a batteria e/o un trasformatore per XC a 24 Vca. Predisposto per installazioni sia all'interno che all'esterno, XC Hybrid è disponibile in modelli con armadietto in plastica o in acciaio inox (a 6 e 12 stazioni). Ciò significa che è la soluzione migliore per un'ampia gamma di applicazioni residenziali e commerciali. Piccole aree residenziali, parchi, giardini, spartitraffico e rotatorie non aspettano che XC Hybrid. Con la memoria permanente e la funzione di backup ‘Easy Retrieve’, c'è la sicurezza di poter recuperare in qualunque momento il programma di irrigazione impostato.

- Alimentato a batterie e/o corrente
- Tipo: Fisso
- Numero di stazioni: 6, 12 (plastica o in acciaio inossidabile)
- Armadietto: Plastica per interni/esterni; acciaio inossidabile per esterni
- Programmi indipendenti: 3
- Partenze giornaliere per programma: 4
- Tempo di funzionamento massimo della stazione: 4 ore
- Gestisce solo solenoidi bistabili a CC (9 V)
- Periodo di garanzia: 2 anni

Compatibile con il Kit Pannello solare [1]

Memoria Easy Retrieve [2]

Partenza manuale con un singolo pulsante [3]

Bypass del sensore pioggia [4]

Ritardo di irrigazione programmabile [5]

Memoria permanente [6]

Regolazione stagionale globale [7]

Ritardo tra Stazioni [8]

Programmabilità sensore [9]

Source URL (retrieved on *01/06/2015 - 19:08*): http://www.hunterindustries.com/it/product/programmatori/xc-hybrid

Links:
[1] http://www.hunterindustries.com/it/node/10001
[2] http://www.hunterindustries.com/it/node/4966
[3] http://www.hunterindustries.com/it/node/5151
[4] http://www.hunterindustries.com/it/node/5186
[5] http://www.hunterindustries.com/it/node/5171
[6] http://www.hunterindustries.com/it/node/5146
[7] http://www.hunterindustries.com/it/node/5086
[8] http://www.hunterindustries.com/it/node/6221
[9] http://www.hunterindustries.com/it/node/5326
[10] http://www.hunterindustries.com/sites/default/files/BR_XCH_it.pdf
[11] http://www.hunterindustries.com/sites/default/files/BR_XCH_dom.pdf
[12] http://www.hunterindustries.com/sites/default/files/BR_XCH_em.pdf
[13] http://www.hunterindustries.com/sites/default/files/BR_XCH_sp.pdf
[14] http://www.hunterindustries.com/sites/default/files/BR_XCH_fr.pdf
[15] http://www.hunterindustries.com/sites/default/files/BR_XCH_PT.pdf
[16] http://www.hunterindustries.com/sites/default/files/BR_XCH_gr.pdf
[17] http://www.hunterindustries.com/sites/default/files/br_xch_tr.pdf
[18] http://www.hunterindustries.com/sites/default/files/br_xch_ru.pdf
[19] http://www.hunterindustries.com/it/global
[20] http://www.hunterindustries.com/sites/default/files/OM_XCH_IT.pdf
[21] http://www.hunterindustries.com/sites/default/files/OM_XCH_DOM.pdf
[22] http://www.hunterindustries.com/sites/default/files/OM_XCH_SP.pdf
[23] http://www.hunterindustries.com/sites/default/files/OM_XCH_FR.pdf
[24] http://www.hunterindustries.com/sites/default/files/OM_XCH_PT.pdf
[25] http://www.hunterindustries.com/sites/default/files/OM_XCH_GR.pdf
[26] http://www.hunterindustries.com/sites/default/files/WS_XCHybrid_Stainless.doc