

Pro-C®

Simple programming and flexible station expansion make the Pro-C Controller the professional's choice for residential and light commercial systems.

KEY BENEFITS

- Number of stations: Conventional wiring from 4 to 23 stations
- Hybrid EZ Decoder option up to 32 total stations (28 stations maximum if two-wire only)
- 3 independent irrigation programs (4 start times each) allow for customized scheduling
- Two sensor inputs come standard for use with Hunter Klik or Solar Sync® Sensors
- Large, backlit display for simple programming and manual operation in any light
- Optional Seconds Mode offers precise watering and flexible Run Times
- Prewired with power cord and plug for simple installation in indoor and outdoor applications
- 1 P/MV output for pump start relay and master valve activation
- Dedicated Solar Sync dial position provides logic for smart water savings
- SmartPort® Wiring Harness ensures quick connection to convenient ROAM and ROAM XL Remotes
-

Operating Specifications

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: IP44, UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 2 years



Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/controllers/pro-cr-042824>