Published on *Hunter Industries* (http://www.hunterindustries.com)

XC Hybrid

XC Hybrid

Controlador híbrido que funciona com pilhas ou energia elétrica

Características | **Modelos** | **Especif.** | **Recursos**

O Controlador XC Hybrid é construído com todas as funções de gestão eficiente de água do Controlador XC e opera solenóides tipo latching (CC) com pilhas ou um transformador de saída de 24 V CA. Preparado para instalações exteriores ou interiores, o XC Hybrid está disponível nos modelos de plástico e aço inoxidável de 6, 12 estações. Isto significa que é a solução certa para uma ampla gama de aplicações residenciais e comerciais. Pequenas áreas residenciais, parques, jardins, faixas centrais de estradas e rotatórias estão preparadas para o XC Hybrid. Com a cópia de segurança de memória 'Easy Retrieve' e memória não volátil incluída, tem a garantia de que irá relembrar todos os programas de irrigação do controlador.

- Funciona a pilhas ou com alimentação elétrica CA
- Número de estações: 6, 12 (plástico ou aço inoxidável)
- Tipo: Fixo
- Caixas: Plástica interna / externa; aço inoxidável externa
- Programas independentes: 3
- Horas de início por programa: 4
- Tempo de execução máximo da estação: 4 h
- Aciona apenas solenóides tipo latching (CC)
- O Painel Solar opcional substitui as pilhas e proporciona o funcionamento sem manutenção.
- Período de garantia: 2 anos

XC Hybrid Compatível com Kit de Painel Solar [1]

Easy Retrieve™ [2]

Início manual com um só toque e avanço [3]

Derivação do sensor de chuva [4]

Atraso de rega programável [5]

Memória não volátil [6]

Regulação sazonal global [7]

Atraso entre estações [8]

Capacidade de programação dos sensores [9]

Source URL (retrieved on *31/03/2015 - 23:10*): http://www.hunterindustries.com/pt/product/controladores/xc-hybrid?source=lang&from=es&to=pt

Links:
[1] http://www.hunterindustries.com/pt/node/12416
[2] http://www.hunterindustries.com/pt/node/12101
[3] http://www.hunterindustries.com/pt/node/12231
[4] http://www.hunterindustries.com/pt/node/12271
[5] http://www.hunterindustries.com/pt/node/12256
[6] http://www.hunterindustries.com/pt/node/12221
[7] http://www.hunterindustries.com/pt/node/12136
[8] http://www.hunterindustries.com/pt/node/12076
[9] http://www.hunterindustries.com/pt/node/12311
[10] http://www.hunterindustries.com/sites/default/files/BR_XCH_PT.pdf
[11] http://www.hunterindustries.com/sites/default/files/BR_XCH_dom.pdf
[12] http://www.hunterindustries.com/sites/default/files/BR_XCH_em.pdf
[13] http://www.hunterindustries.com/sites/default/files/BR_XCH_sp.pdf
[14] http://www.hunterindustries.com/sites/default/files/BR_XCH_it.pdf
[15] http://www.hunterindustries.com/sites/default/files/BR_XCH_fr.pdf
[16] http://www.hunterindustries.com/sites/default/files/BR_XCH_gr.pdf
[17] http://www.hunterindustries.com/sites/default/files/br_xch_tr.pdf
[18] http://www.hunterindustries.com/sites/default/files/br_xch_ru.pdf
[19] http://www.hunterindustries.com/pt/global
[20] http://www.hunterindustries.com/sites/default/files/OM_XCH_PT.pdf
[21] http://www.hunterindustries.com/sites/default/files/OM_XCH_DOM.pdf
[22] http://www.hunterindustries.com/sites/default/files/OM_XCH_SP.pdf
[23] http://www.hunterindustries.com/sites/default/files/OM_XCH_IT.pdf
[24] http://www.hunterindustries.com/sites/default/files/OM_XCH_FR.pdf
[25] http://www.hunterindustries.com/sites/default/files/OM_XCH_GR.pdf