

IRRIGATION LEGEND

PRODUCT DESCRIPTION
HUNTER I-20-04-XXI-20-06-XX NOZZLE AS SHOWN
NOZZLE PERFORMANCE:

#3.5 @ 40 PSI - 3.0 GPM 38' RADIUS #6 @ 40 PSI - 4.9 GPM 40' RADIUS #8 @ 40 PSI - 6.0 GPM 41' RADIUS #10 @ 40 PSI - 8.4 GPM 42' RADIUS

HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZED AS SHOWN

HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 75 GPM IS 2.0"
BACKFLOW PREVENTER SIZED TO SYSTEM GPM HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL) HUNTER ACC-1200 SOLID STATE METAL CABINET CONTROLLER

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON .75" SCH 80 SWING JOINTS
 ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS

RECOMMENDATIONS

- IRRIGATION NOTES
- HATERAL PIPE

 SLEEVING

 SOLATION VALVE LINE SIZED

 HFS HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
 6. LATERAL DEPTH TO BE NO LESS THAN 16"
 7. ELECTRIC CONTROL VALVES TO BE COVER
 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAF! 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF 10. QCV TO BE LOCATED IN 10" VALVE BOX ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
- 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA

ZONE A1 A2 A3 A4 A5 A6 A7 A8 A9 A10 A11

STATION NUMBER

PRECIPITATION RATE VALVE SIZE

79 80 80 83 83 83 83 78 78 1221221222

Hunter Industries 1940 Diamond Street
San Marcos, California 92078
SpecPro Technical Assistance
1-800-319-4796
www.HunterIndustries.com

OFFICIAL BASEBALL FIELD

I-20 SIX ROW DESIGN LOOPED MAINLINE



SHEET

OF 1