

IRRIGATION LEGEND

PRODUCT DESCRIPTION

HUNTER I-40-04-SS-ON-XX/I-40-06-SS-ON-XX, NOZZLE AS SHOWN

HUNTER I-40-04-SS-ON-XXII-40-06-SS-UN-XX, NOZZLE AS SHOWN
 HUNTER I-40-04-SS-XXII-40-06-SS-XX, NOZZLE AS SHOWN

#10@ 80 PSI - 13.0 GPM 51' RADIUS #13 @ 80 PSI - 14.2 GPM 53' RADIUS #13 @ 80 PSI - 14.2 GPM 65' RADIUS #23 @ 80 PSI - 24.5 GPM 65' RADIUS #280N @ 80 PSI - 30.9 GPM 72' RADIUS

HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZED AS SHOWN HUNTER HC-44-XX-AW QUICK COUPLER VALVE (OPTIONAL) SHOWN HUNTER IC-1200 SOLID STATE METAL CABINET CONTROLLER HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 98 GPM IS 2.0"

BACKFLOW PREVENTER SIZED TO SYSTEM GPM

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
 ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS
- RECOMMENDATIONS
 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
 6. LATERAL DEPTH TO BE NO LESS THAN 16"
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
 8. LOCATE VALVES/OCVS OUT OF HIGH TRAFFIC AREAS
 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
 10. OCV TO BE LOCATED IN 10" VALVE BOX
- ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,
- FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS
 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
- 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA 82 P 111112222333

1 03 1 03 1 03 1 03 1 03 1 03 58

PRECIPITATION RATE VALVE SIZE GPM STATION NUMBER

OFFICIAL BASEBALL FIELD

I-40 FOUR ROW DESIGN



SHEET

1 OF 1

Hunter Industries Hunter Industries 1940 Dlamond Street San Marcos, Callfornia 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com