

IRRIGATION LEGEND

PRODUCT DESCRIPTION
HUNTER I-20-06-SS-XX NOZZLE AS SHOWN
HUNTER I-35-06-SS-XX NOZZLE AS SHOWN
HUNTER I-35-06-SS-XX NOZZLE AS SHOWN

NOZZLE PERFORMANCE: 1.20. #1 @ 40 PSI - 1.0 GPM 31' RADIUS #2 @ 40 PSI - 1.8 GPM 34' RADIUS 1-35 LP. #7 @ 40 PSI - 7.5 GPM 45' RADIUS #16 @ 40 PSI - 14.7 GPM 55' RADIUS

● HUNTER ICY/BV ELECTRIC CONTROL VALVE SIZE AS SHOWN
● HUNTER HO_44-XX_AM QUICK COUPLER VALVE (OPTIONAL)
② HUNTER C-1200 SOLID STATE METAL CABINET CONTROLLER
③ HUNTER SOLAR-SYNG-SEN ON SITE WEATHER SENSORS
⑤ WATER METER MINIMUM SIZE @ 73 GPM IS 2.0*
⑤ WATER METER MINIMUM SIZE @ 73 GPM IS 2.0*
⑥ BACKFLOW PREVENTER SIZED TO SYSTEM GPM

— MANULUR EIPPE

— SLEEVING
② ISOLATION VALVE LINE SIZED

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
 ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS

- 10. QCV TO BE LOCATED IN 10" VALVE BOX
 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,
- FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS

 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS

 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE

 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SYSTEM PERFORMANCE DATA

GPM STATION NUMBER

PRECIPITATION RATE VALVE SIZE

SHEET 양 1

OFFICIAL LITTLE LEAGUE FIELD

I-35LP FOUR ROW DESIGN

Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com