

FOUR ROW DESIGN

-35

FIELD

SOFTBALL

1940 Dlamond Street
Marcos, California 92078
ccPro Technical Assistance
1-800-319-4796
www.HunterIndustries.com

SHEET 1 OF 1

IRRIGATION LEGEND

PRODUCT DESCRIPTION

HUNTER I-35-06-SS-B-XX, NOZZLE AS SHOWN HUNTER I-35-06-SS-B-XX, NOZZLE AS SHOWN

NOZZLE PERFORMANCE: #9 @ 5.0 Bars - 37.8 l/min 15.5m RADIUS #15 @ 5.5 Bars - 61.5 l/min 17.7m RADIUS #18 @ 5.5 Bars - 68.5 l/min 19.2m RADIUS

HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN
HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)

HUNTER IC-1200-M SOLID STATE METAL CABINET CONTROLLER

HUNTER SOLAR-SYNO-SEN ON SITE WEATHER SENSOR

M WATER METER MINIMUM SIZE @ 274 I/min IS Sam

BACKFLOW PREVENTER SIZED TO SYSTEM I/min

MAINLINE PIPE

LATERAL PIPE

LATERAL PIPE

SLEEVING

WATER REQUIREMENT

63

63

75

50

A3

69

1"

53.1

175

63

A5

274

1.5"

27.9

WATER REQUIREMENT AT

FIFLD FLEVATION

-DOWNSTREAM OF

BACKFLOW

50

50

8A

185

1.5"

14.4

50

63

A1

175

1.5"

27.9

- 50

17.0m typ.

50

63

A6

206

1.5"

24.3

50

Α7

246

1.5"

14.4

17.2m typ.

50

15

-WITHIN 30m OF FIELD

IS 274 I/min @ 6.06 Bars

SISOLATION VALVE LINE SIZED

IRRIGATION NOTES

- 1. SPRINKLER LOCATIONS ARE TO SCALE
- 2. PIPE LOCATIONS ARE DIAGRAMMATIC
- 3. ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING JOINTS
- 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS
- 5. MAINLINE DEPTH TO BE NO LESS THAN 460mm
- 6. LATERAL DEPTH TO BE NO LESS THAN 410mm
- 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX
- 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS
- 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
- 10. QCV TO BE LOCATED IN 10" VALVE BOX
- 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
- 13. REFER TO HUNTER INSTALLATION DETAILS
- 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICATIONS
- 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
- 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SPRINKLER PERMFORMANCE DATA

· · · ·		`			· · ·		-
ZONE	SIZE		ow	PR	DU	SC(10% WINDO	'n
A1 A2 A3 A4 A5	1.5" 1.5" 2-1" 1.5" 1.5"	m²/hr 10.5 10.5 8.2 12.3 16.4 12.3	l/mln 175 175 137 206 274 206	mm/hr 27.9 27.9 53.1 27.9 27.9	.80 .80 .80 .80	1.3 1.3 1.3 1.3	
A6 A7 A8 A9	1.5" 1.5" 1.5" 1.5"	14.8 14.8 11.1 14.8	246 185 246	24.3 14.4 14.4 14.4	80 86 86 86	1.3 1.2 1.2 1.2	

VALVE ID GUIDE

A1	STATION NUMBER					
273	I/min					
1.5"	VALVE SIZE					
19.0	PRECIPITATION RATE mm.					

0 10m 20m 5m 15m

A3 69

1"

53.1

A4

206

1.5"

27.9

A9

246

1.5"

14.8

A2

175 1.5" 27.9

75

63

63

50

⊗⊕

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified imgation designer be consulted.