

## IRRIGATION LEGEND

PRODUCT DESCRIPTION

HUNTER I-20-6P-ADS-XX NOZZLE AS SHOWN
 HUNTER I-35-06-SS-XX NOZZLE AS SHOWN
 HUNTER I-35-06-SS-XX NOZZLE AS SHOWN

NOZZLE PERFORMANCE:

#SR1.5 @ 40 PSI - 1.5 GPM 25' RADIUS #SR.75 @ 40 PSI - .75 GPM 25' RADIUS

#7 @ 40 PSI - 7.5 GPM 45' RADIUS #15 @ 40 PSI - 14.7 GPM 55' RADIUS

 ♣ HUNTER HQ-44-XX-AW QUICA COLLID STATE METAL CABINE! COLLID STATE METAL CABINE! COLLID STATE METAL CABINE! COLLID STATE METAL CABINE! COLLID STATE WEATHER SENSOR
 ★ HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR
 ★ WATTER METER MINIMUM SIZE @ 59 GPM IS 1.5"
 ■ BACKFLOW PREVENTER SIZED TO SYSTEM GPM
 ★ ATERAL PIPE HUNTER ICVIBV ELECTRIC CONTROL VALVE SIZE AS SHOWN HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)

HUNTER ACC-1200 SOLID STATE METAL CABINET CONTROLLER

HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

## **IRRIGATION NOTES**

- SPRINKLER LOCATIONS ARE TO SCALE
- PIPE LOCATIONS ARE DIAGRAMMATIC ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
- 1. SPRINKLER LOCATIONS ARE TO SCALE
  2. PIPE LOCATIONS ARE DIAGRAMMATIC
  3. ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
  4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS

- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
  6. LATERAL DEPTH TO BE NO LESS THAN 10"
  7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE BOX 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
- 10. QCV TO BE LOCATED IN 10" VALVE BOX
  11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
  12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,
- FEDERAL CODES

- 13. REFER TO HUNTER INSTALLATION DETAILS
  14. REFER TO HUNTER CATALOR PERFORMANCE SPECIFICATIONS
  15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
  16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

## VALVE ID GUIDE

50"/hr	1.5	55	Α1	
PRECIPITATION RATE	VALVE SIZE	GPM	STATION NUMBER	

## SYSTEM PERFORMANCE DATA

пi					
A9 A10	8 4 8	8 4 8 8	ZONE A2		
		1 5 1 5 1 2 1 5 1 2 1 5			
59	59 44	37 14.7 59	FLOW 20.8 37		
46	46 4 00	194	9 5 R		
75	75 75	75 68	85 68		
1.5	1 1 4	2 2 2 5	SC (10% WINDOW) 1.2 1.5		

Hunder Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plan. Because of the many valables of every system and of every late we recommend that a qualified in gathor designer be consulted.

SHEET

1 OF 1

Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

OFFICIAL SOFTBALL FIELD

I-35LP FOUR ROW DESIGN LOOPED MAINLINE

