

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING
- HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"
- --- MAINLINE PIPE
 --- LATERAL PIPE
 --- SLEEVING
 ⊗ ISOLATION VALVE LINE SIZED
 H#S HUNTER FLOW SENDON

 - HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN HUNTER HCA44-XX-AW QUICK COUPLER VALVE (PPTONAL) HUNTER IC-800-M SOLID STATE METAL CABINET CONTROLLER HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METAR MINIMUM SIZE @ 130 Jimin IS 50mm BACKFLOW PREVENTER SIZED TO SYSTEM Jimin BACKFLOW PREVENTER SIZED TO SYSTEM Jimin
- HUNTER I-40-04-SS-HS-B-XX/I-40-06-SS-HS-B-XX, NOZZLE AS SHOWN HUNTER I-40-04-SS-HS-B-XX/I-40-06-SS-HS-B-XX, NOZZLE AS SHOWN PRODUCT DESCRIPTION NOZZLE PERFORMANCE: #15 @ 5.0 Bars - 64.9 I/min 16.2m RADIUS

IRRIGATION LEGEND

VALVE ID GUIDE

WATER REQUIREMENT AT
-FIELD ELEVATION
-WITHIN 30m OF FIELD
-DOWNSTREAM OF
BACKFLOW
IS 130 I/min @ 5.62 Bars

25552 151151 SE

FLOW min / I/min 7.8 130 7.8 130 7.8 130 7.8 130 3.9 64.9

PR 50.5 50.5 25.1 25.1 12.5

WATER REQUIREMENTS

SYSTEM PERFORMANCE DATA

VALVE SIZE

STATION NUMBER

PRECIPITATION RATE mm/hr

Humer Industries offers this plain as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plain. Because of the many variables of every system and of every site we recommend that a qualified impation designer be consulted.

SHEET **1** OF

Hunter Industries 1940 Diamond Street San Marcos, Callfornia 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com

CLAY TENNIS COURT

8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF 10. QCV TO BE LOCATED IN 10" VALVE BOX 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM

13. REFER TO HUNTER INSTALLATION DETAILS
14. REFER TO HUNTER CATALOG FOR PERFORMANCE

SPECIFICATIONS

12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE

FEDERAL CODES

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

RECOMMENDATIONS
5. MAINLINE DEPTH TO BE NO LESS THAN 460mm
6. LATERAL DEPTH TO BE NO LESS THAN 410mm
7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE

JOINTS
4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS

I-40 HIGH SPEED DESIGN

