

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION
•	Hunter ICV-G 1-1/2" 1", 1-1/2", 2", and 3" Plastic Electric Remote Control Valves, Globe Configuration, with NPT Threaded Inlet/Outlet, for Commercial/Municipal Use.
•	Hunter ICV-G 2" 1", 1-1/2", 2", and 3" Plastic Electric Remote Control Valves, Globe Configuration, with NPT Threaded Inlet/Outlet, for Commercial/Municipal Use.
BF	Watts LF909M1 1-1/4" Lead Free Reduced Pressure Backflow Preventer.
A2C 750-SS	Hunter A2C-75D-SS 75-Station Decoder controller in a stainless steel wall mount enclosure.
М	Water Meter 2"
	Irrigation Lateral Line: PVC Class 200 SDR 21 2"
	Irrigation Lateral Line: PVC Class 200 SDR 21 2 1/2"
	Irrigation Lateral Line: PVC Class 200 SDR 21 3"
	Irrigation Lateral Line: PVC Class 200 SDR 21 4"
	Irrigation Mainline: PVC Class 315 SDR 13.5
	Irrigation Mainline: PVC Class 315 SDR 13.5 3"
	Irrigation Mainline: PVC Class 315 SDR 13.5 6"

## **IRIRGATION LEGEND**

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION	QTY	PSI	GPM
(25)	Hunter I-50-06-SS Turf Rotor, 6.0" Pop-Up. Adjustable to Full Circle. Drain Check Valve, Stainless Steel Riser, 1" Female NPT Inlet Threads, Standard Nozzle.	18	80	27.7
(28)	Hunter I-50-06-SS-ON Turf Rotor, 6.0" Pop-Up. Adjustable to Full Circle. Drain Check Valve, Stainless Steel Riser, 1" Female NPT Inlet Threads, Dual Opposing Nozzle.	10	80	30.9

Sc	ale: 1"	= 40'		
F	łF			1
J				
_ 0	10'	20'	40'	80'

TECHNICAL ASSISTANCE 1-800-319-4796 WWW.HUNTERINDUSTRIES.COM

Hunter Industries offers this plan as a general guide for estimating purposes and offers no indemnity, expressed or implied, for projects installed from this plan. Consult a qualified irrigation designer to account for system and site variables.