


## SRV - CN

Simple, Reliable, and Economical Residential Valve Built To Handle Tough Conditions



- Application: Residential
- Size: 1" (25 mm)
- Double-beaded diaphragm seal design for superior leak-free performance
- Compatible with Hunter's DC Latching solenoids for use with battery operated controllers
- Captive bonnet bolts provide hassle-free valve maintenance
- Low flow capability allows use of Hunter's micro-irrigation products
- Encapsulated 24 VAC solenoid with captive plunger for hassle-free service
- Temperature rating: 66° C
- Warranty period: 2 years



### Operating Specifications

- Flow rate: 0.25 to 9 m<sup>3</sup>/hr; 4 to 150 l/min
- Recommended pressure range: 1.5 to 10 bar; 150 to 1000 kPa

### Solenoid Specifications

- 24 VAC solenoid
  - 350 mA inrush, 190mA holding, 60 cycles
  - 370 mA inrush, 210mA holding, 50 cycles

### User Installed Options

- Solenoid conduit cover (P/N 464322)
- DC latching solenoid (P/N 458200)
- Accu-Sync pressure regulator

## SRV PRESSURE LOSS IN PSI

<b>Flow</b>	<b>1"</b>
<b>GPM</b>	<b>Globe</b>
1	1.1
5	1.9
10	1.9
15	1.6
20	5.0
30	9.1
35	16
40	20

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/cn/irrigation-product/discontinued-models/srv-cn-071724>