

Drip Control Zone Kits

Durable, All-in-One Control Zone Kits for Residential and Commercial Applications

KEY BENEFITS

- Factory-assembled for quick and easy installation
- All Hunter valves are water-tested to ensure dependable operation
- All Senninger regulators are water-tested and provide the most accurate and dependable pressure regulation in the industry
- All kits come standard with a stainless steel 150-mesh screen
- Wide range of kits cover applications with low, medium, and high ranges
- Some models are available with reclaimed components



User-Installed Options

- Reclaimed water ID handle for PCZ-101 (P/N 269205)

Operating Specifications

- Pressure regulation: 1.7 or 2.8 bar; 170 or 280 kPa
- Flow: 2 to 55 l/min
- Operating pressure: 1.4 to 8.0 bar; 140 to 800 kPa
- Operating temperature: up to 66°C
- 150-mesh (100-micron) stainless steel screen

Solenoid Operating Specifications

- Heavy-duty solenoid: 24 VAC
 - 350 mA inrush current, 190 mA holding current, 60 Hz
 - 370 mA inrush current, 210 mA holding current, 50 Hz
- Warranty period: 2 years

Copyright © 2023 Hunter Industries™. All rights reserved.

<https://www.hunterindustries.com/en-metric/irrigation-product/micro-irrigation/drip-control-zone-kits-120423>