

# Eco-Wrap

Irrigate more efficiently than blank dripline with fleece-wrapped dripline.

## KEY BENEFITS

- Perfect for narrow areas that are difficult to irrigate with standard methods
- Anti-siphon feature and fleece wrap protect against debris and root intrusion
- Saves 20–40% more water than standard products due to superior capillary movement of water to the entire root zone, promoting healthier root growth
- Non-draining, pressure-compensating emitters open/close simultaneously, maximising efficiency
- Check height of 1.5 m minimises system drainage and runoff



## Operating Specifications

- Operating range: 1.0 to 3.5 bar; 100 to 350 kPa
- Minimum filtration: 120 mesh; 125 microns
- Air relief recommended for sloping conditions greater than 1.5 m
- Recommended installation depth: turf (10–16 cm); other (10–30 cm)
- Compatible with Eco-Mat
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)

## Product Specifications

- Flow rate: 2.1 l/hr
- Emitter spacing: 30 cm
- Tubing dimensions: 0.660" x 0.560" (outside/inside diameter)
- Roll length: 16 mm = 100 m; 17 mm = 90 m
- Accepts 16 mm barb or LOC fittings

### Eco-Wrap Dimensions Chart

ECO-WRAP TECHNICAL SPECIFICATIONS

	16mm	17mm
<b>Flow</b>	2.2 l/hr; 0.13 m <sup>3</sup> /hr	2.2 l/hr; 0.13 m <sup>3</sup> /hr
<b>Roll Length</b>	100 m	76 m

	<b>16mm</b>	<b>17mm</b>
<b>Operating Pressure</b>	1.0 to 3.5 bar; 100 to 350 kPa	1.0 to 3.5 bar; 100 to 350 kPa
<b>Minimum Filtration</b>	120 mesh	120 mesh
<b>Emitter Spacing</b>	30 cm	30 cm

Copyright © 2023 Hunter Industries™. All rights reserved.

<https://www.hunterindustries.com/en-metric/irrigation-product/micro-irrigation/eco-wrap>  
120623