

Filters & Filter Regulators

Choose rugged filters and filter regulators with stainless steel screens for maximum performance.

KEY BENEFITS

- HFR-075 (Hunter Filter Regulator)
 - - Compact, all-in-one filter and regulator minimise required valve box space
 - - Senninger regulator provides precise regulation to protect system from high pressure
 - - 150 mesh (100 microns) stainless steel screen for years of reliable filtration
 - - Wide flow range covers most drip applications
- HY-075 (Hunter Y-Filter)
 - - 150 mesh (100 microns) stainless steel screen for years of reliable filtration - Wide flow range covers most drip applications



OPERATING SPECIFICATIONS

- HFR-075
 - Pressure regulation: 1.7 or 2.8 bar; 170 or 280 kPa
 - Flow: 2 to 55 l/min
 - Operating pressure: 1.4 to 8.0 bar; 140 to 800 kPa
 - Operating temperature: up to 66° C
- HY-075
 - Flow: up to 75 l/min
 - Operating pressure: up to 8.0 bar; 800 kPa
 - Operating temperature: up to 66°C
- Warranty period: 2 years

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/en-metric/irrigation-product/micro-irrigation/filters-filter-regulators>
072724