

ST-1200-BR

The cost-effective ST-1200-BR Synthetic Turf Rotor is the ideal riser-mount solution for pastures, corrals, arenas, dust control, and wash-down watering.

VENTAJAS PRINCIPALES

- Nozzle choices: 5 (included)
- Standard nozzle: 12
- Nozzle range: 10 to 18
- Nozzle trajectory: 22.5°
- Isolated, grease-lubricated gear drive
- Nozzle barrels: short and long (included)
- Movable stops (left and right) arc adjustment
- Arc setting: 40° to non-reversing 360°
- Ratcheting nozzle turret



OPERATING SPECIFICATIONS

- Radius: 67' to 115'
- Flow: 27.0 to 131.0 GPM

USER INSTALLED OPTIONS

- Adapter, 1.5" male spigot x 1.5" male BSP: P/N 241401SP
- NPT adapters are N/A; we recommend contacting the [local dealer](#) for additional sourcing.

ST-1200-BR Nozzle Performance Data

ST-1200BR Nozzle Performance Data

Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr	
				■	▲
10 • Black	30	67	27.0	1.16	1.34
	45	75	32.8	1.12	1.30
	60	85	38.1	1.02	1.17
	75	90	43.5	1.03	1.19
12 • Black	30	68	33.6	1.40	1.62

45	78	41.2	1.30	1.51	
60	88	47.6	1.18	1.37	
75	98	53.1	1.06	1.23	
14 • Black	30	70	45.7	1.80	2.07
	45	86	56.0	1.46	1.68
	60	100	64.7	1.25	1.44
	75	110	72.5	1.15	1.33
16 • Black	30	72	59.5	2.21	2.55
	45	93	73.0	1.62	1.88
	60	103	84.3	1.53	1.77
	75	116	80.9	1.16	1.34
18 • Black	30	95	92.5	1.97	2.28
	45	104	107.0	1.90	2.20
	60	111	119.5	1.87	2.16
	75	115	131.0	1.91	2.20

Copyright © 2023 Hunter Industries™. All rights reserved.

<https://www.hunterindustries.com/irrigation-product/st-system/st-1200-br-120623>