

## MP Rotator® MP800 Nozzle

The MP800 offers a higher precipitation rate perfect for small spaces and spray retrofits.

### KEY BENEFITS

- Precipitation rate of approximately 0.8 in/hr for spray retrofit applications
- Automatic matched precipitation for simplified irrigation design and flexibility
- Double-pop feature protects the nozzle from external debris
- High distribution uniformity for a healthy landscape with maximum water efficiency
- Wind-resistant, multi-stream technology prevents misting
- Adjustable arc only when MP Rotator Nozzle is running for vandal resistance
- Removable filter screen prevents nozzle clogging
- Color-coded for easy identification



### OPERATING SPECIFICATIONS

- Radius reduction up to approximately 25% on all models
- Recommended operating pressure: 40 PSI
- Minimum radius setting achieved at 30 PSI
- Filtration recommended on dirty water applications
- Warranty period: 3 years





### OPTIONS

- Pair with Pro-Spray® PRS40 pop-up for pressure regulation to 40 PSI for nominal radius settings
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 30 PSI for minimum radius settings

MP800SR

---

**Radius:** 6' to 12'  
**Adjustable Arc & Full Circle**  
**Orange and Gray:** 90° to 210°  
**Lime Green and Gray:** 360°

Arc	Pressure	Max Radius							Min Radius	
		Radius	Flow		Precip in/hr		Radius	Flow		
			ft	GPM	GPH	■			▲	ft.
90° 	30		8	0.17	9.6	0.90	1.04	6	0.13	
	35		9	0.21	11.4	0.89	1.03	7	0.15	
	<b>40</b>		<b>10</b>	<b>0.23</b>	<b>13.8</b>	<b>0.83</b>	<b>0.96</b>	<b>8</b>	<b>0.16</b>	
	45		11	0.25	15.0	0.80	0.92	8	0.18	
	50		11	0.27	16.2	0.79	0.92	9	0.19	
	55		12	0.28	16.8	0.80	0.93	10	0.20	
180° 	30		8	0.33	19.2	0.88	1.02	6	0.26	
	35		9	0.38	22.2	0.85	0.99	7	0.29	
	<b>40</b>		<b>10</b>	<b>0.42</b>	<b>25.2</b>	<b>0.81</b>	<b>0.93</b>	<b>8</b>	<b>0.32</b>	
	45		11	0.46	27.6	0.77	0.88	8	0.36	
	50		11	0.48	28.8	0.76	0.88	9	0.38	
	55		12	0.50	30.0	0.73	0.84	10	0.40	
210° 	30		8	0.35	22.2	0.80	0.93	6	0.30	
	35		9	0.38	26.4	0.77	0.89	7	0.34	
	<b>40</b>		<b>10</b>	<b>0.43</b>	<b>29.4</b>	<b>0.81</b>	<b>0.91</b>	<b>8</b>	<b>0.37</b>	
	45		10	0.45	31.8	0.82	0.95	8	0.42	
	50		11	0.49	33.6	0.73	0.85	9	0.44	
	55		12	0.56	34.8	0.70	0.81	10	0.47	
360° 	30		8	0.66	37.8	0.89	1.03	6	0.47	
	35		9	0.71	42.0	0.80	0.92	7	0.52	
	<b>40</b>		<b>10</b>	<b>0.78</b>	<b>46.8</b>	<b>0.79</b>	<b>0.91</b>	<b>8</b>	<b>0.56</b>	
	45		10	0.85	51.0	0.78	0.90	8	0.59	
	50		11	0.88	52.8	0.73	0.85	9	0.63	
	55		12	0.98	58.8	0.70	0.81	10	0.70	

**Bold** = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Hunter PRS40 Spray Body, pressure regulated at 40 PSI.

\* Flow and precipitation rates may change as a result of reducing radius.

## MP815











**Radius:** 8' to 16'

Adjustable Arc & Full Circle

**Maroon and Gray:** 90° to 210°

**Lt. Blue and Gray:** 210° to 270°

**Olive and Gray:** 360°

Arc	Pressure		Radius	Flow		Precip in/hr	
	PSI			ft	GPM	GPH	■
90° 	30		14	0.42	25.2	0.83	0.95
	35		15	0.46	27.6	0.79	0.91
	40		15	0.49	29.4	0.84	0.97
	45		16	0.52	31.2	0.78	0.90
	50		16	0.55	33.0	0.83	0.96
	55		16	0.58	34.8	0.87	1.01
180° 	30		13	0.75	45.0	0.85	0.99
	35		14	0.86	51.6	0.84	0.98
	40		15	0.93	55.8	0.80	0.92
	45		15	0.96	57.6	0.82	0.95
	50		16	1.06	63.6	0.80	0.92
	55		16	1.11	66.6	0.83	0.96
210° 	30		13	0.88	52.8	0.86	0.99
	35		14	0.96	57.6	0.81	0.93
	40		15	1.10	66.0	0.81	0.93
	45		15	1.16	69.6	0.85	0.98
	50		16	1.24	74.4	0.80	0.92
	55		16	1.30	78.0	0.84	0.97
270° 	30		13	1.14	68.4	0.87	1.00
	35		14	1.24	74.4	0.81	0.94
	40		15	1.40	84.0	0.80	0.92
	45		15	1.47	88.2	0.84	0.97
	50		16	1.54	92.4	0.77	0.89
	55		16	1.61	96.6	0.81	0.93
360° 	30		13	1.52	91.2	0.87	1.00
	35		14	1.70	102.0	0.83	0.96
	40		15	1.87	112.2	0.80	0.92
	45		15	2.00	120.0	0.86	0.99
	50		16	2.13	127.8	0.80	0.92
	55		16	2.26	135.6	0.85	0.98

**Bold** = Optimal pressure for the MP Rotator is 40 PSI. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40, pressure regulated at 40 PSI.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterindustries.com/irrigation-product/mp-rotator/mp-rotatorrr-mp800-nozzle>  
072724