

1" PGV

Highly versatile, robust irrigation valves for simple installation and serviceability. 100% of Hunter valves are water-tested.

KEY BENEFITS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Captive bonnet screws eliminate the possibility of lost parts during disassembly
- Triple-tool bonnet screws are compatible with standard or Phillips screwdrivers as well as a nut driver
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximizes efficiency and prolongs the life of the system



User-Installed Options

- Accu Sync® pressure regulation at the valve*
- DC-latching solenoid for battery-powered controllers (P/N 458200)
- Solenoid conduit cover (P/N 464322)

Factory-Installed Options

- LS: Valve without solenoid
- DC: DC-latching solenoid for battery-powered controllers

Operating Specifications

- Flow: 0.2 to 40 GPM
- Recommended pressure range: 20 to 150 PSI
- Temperature rating: 150°F
- Warranty period: 2 years

Solenoid Specifications

- 24 VAC solenoid

- 350 mA inrush, 190 mA holding, 60 Hz
- 370 mA inrush, 210 mA holding, 50 Hz

Copyright © 2023 Hunter Industries™. All rights reserved.

<https://www.hunterindustries.com/en-metric/irrigation-product/valves/1-pgv-120923>