

## ST-1600-KIT: GEAR-DRIVEN ROTOR

ITEM	DESCRIPTION	CATALOG NO.
1	High-speed pop-up, adjustable arc (40°–360°), 2" BSP inlet	ST-1600-HS-B
2	Composite vault, precast hole for rotor and two quick-access ports for quick coupler and remote on-off-auto selector	ST-243636-B
3	Rotor vault hanger and grade adjustment bracket for ST-1600-HS-B Rotor	ST-BKT-1600
4	Manifold butterfly valve and Victaulic® coupling fitting kit	ST-BVF30-K
5	3" metal control valve, 3" grooved Victaulic inlet/outlet fittings, solenoid, and on-off-auto selector manifold	ST-V30-KV
6	Ultra-flexible 3" x 26" stainless steel corrugated manifold inlet hose with stainless steel braided outer support layer with 3" female NPT inlet	ST-H30-K
7	Adjustable manifold support stand; <b>two required per vault</b>	ST-SPT-K
8	Infill barrier system Rubber Cover Kit for ST-1600-HS-B Rotor	ST-IBS-1600
9	Hanger bracket for HQ-5-RC Quick Coupler	ST-BKT-QCV
10	Quick Coupler, 1" NPT inlet, 1/4" outlet for key	HQ-5R-C
11	AC Solenoid Kit, includes solenoid and solenoid base	ST-SSA
12	DC Solenoid Kit, includes solenoid and solenoid base	ST-LSA
13	Remotely located solenoid and on-off-auto selector manifold. Includes ST-SSA, tubing, and ST-SSA hanger bracket	ST-V2030-KIT
14	Filter bolt for the control valve (Not shown)	10005600SP
15	Gear-Drive Removal/Installation Tool	517600SP
16	ST-approved adhesive for attaching artificial turf, track, or ST-FRP-1600 to Infill Barrier System (Not shown)	ST-ADH-K
17	Simulated Concrete Cover	ST-FRP-1600

