



- 01 **Fast:** Immediately shuts off irrigation when high winds are detected
- 02 **Smart:** Keeps pedestrian paths and roadways safe when wind speeds increase
- 03 **Convenient:** Eliminates the need to manually shut off irrigation

WIND-CLIK® WIND SENSOR

Control irrigation system operation during high-wind conditions

Look at any sprinkler's performance chart and you'll see that the data was gathered from tests conducted under no-wind conditions. Of course, in the real world, not every day is calm. While most sprinklers can still perform at close to peak efficiency with some type of breeze, when the air movement starts to get stronger, water coverage can become challenging, questionable, and downright messy. Liability issues can arise if windblown sprinklers soak pedestrian paths or roadways with passing cars.

The Hunter Wind-Clik sensor shuts off irrigation systems during windy conditions (shutdown points are adjustable), and automatically resets the system when conditions are more favorable. With Wind-Clik, you'll save water, worry, and money as your system will only operate when you can be sure that the water intended for your landscape will reach its destination. For effective irrigation control, you'll be blown away by Wind-Clik, instead of simply seeing your water blown away by the wind.

WIND-CLI[®] FEATURES & SPECIFICATIONS

Features

- Shuts off irrigation when winds are high
- Works well with fountains to eliminate overspray in windy conditions
- Installs easily on automatic irrigation systems with quick adjustments
- Compatible with most normally open or normally closed irrigation controllers
- Adjusts to actuate at various wind speeds; sets to shut down system from 12 to 35 mph
- Adjustable reset wind speeds; sets from 8 to 24 mph, based on local conditions

Specifications

- Switch rating (24 VAC): 5 A maximum
- Wind vane diameter: 5"
- Reset speed: 8 to 24 mph
- Includes 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Mounts: Slip fits over 2" PVC pipe or attaches to ½" conduit with adapter
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

WIND-CLI[®]

Model	Description
WIND-CLI [®]	Wind Sensor

Model

WIND-CLI[®]

Height: 4"

Wind vane diameter: 5"



Wind-Click can also be used to turn off fountains during high winds, which prevents overspray onto walkways, increases safety, and reduces liability.

Website hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

© 2020 Hunter Industries Inc. Hunter, the Hunter logo, and all other trademarks are property of Hunter Industries, registered in the U.S. and other countries.  Please recycle.

Gene Smith

Gene Smith, President, Landscape Irrigation and Outdoor Lighting

