

# 1½" ICZ

The toughest plastic valve available comes backed by glass-filled construction, a fabric-reinforced diaphragm, and a double-beaded diaphragm seal.

## KEY BENEFITS

- Highest-quality components set Hunter kits apart
- Highest flow options in the industry
- Factory-assembled to save installation time
- Filter Sentry diaphragm screen cleaning system

## USER-INSTALLED OPTIONS

- Reclaimed water ID handle (P/N 561205)

## ICZ-151-XL

- Pressure regulation: 40 PSI
- Flow: 20 to 60 GPM
- Operating pressure: up to 120 PSI
- Operating temperature: up to 120°F
- 150 mesh; 100 micron stainless steel screen
- 1½" inlet x 2" outlet



## ICZ-151-XL

Height: 12"  
Width: 5½"  
Length: 22½"  
1½" inlet x single 2" outlet

## SOLENOID OPERATING SPECIFICATIONS

- Heavy-duty solenoid: 24 VAC
  - 350 mA inrush current, 190 mA holding current, 60 cycles
  - 370 mA inrush current, 210 mA holding current, 50 cycles
- Warranty period: 5 years
- Additional charts on **page 201**

## DRIP CONTROL ZONE KITS

Model	Description
ICZ-151-40-XL	1½" ICV globe valve with 1½" filter and single 2" regulator

## ICZ-151-40-XL

GPM	Required Pressure for 40 PSI Outlet
20	46
30	50
40	54
50	63
60	75
70	82

For inlet pressures below 60 PSI, pressure regulation may not be required