

ACC-99D

Number of Stations: **1 to 99**
Type: **Decoder**

FEATURES

- Includes all features of the ACC controller, plus decoder operations
- Built in Solar Sync®
- Decoder station sizes available: 1, 2, 4, 6
- Sensor decoder available with Flow and Klik inputs
- Max. recommended distance, decoder to solenoid: 150'
- ICD-HP wireless handheld programmer compatible
- Two-way communications
- Surge suppression: Internal (ground wire included)
- Dual P/MV outputs may be assigned to decoders
- Wire path connectors included with each decoder
- Number of wire paths: 6
- Automatic daily weather-based scheduling with optional Hunter Solar Sync sensor
- ▶ Seasonal Adjustment: Global, by Program, or Solar Sync
- ▶ Programmable decoders
- ▶ Solar Sync Delay

ELECTRICAL SPECIFICATIONS

- Transformer input: 120/230 VAC, 50/60 Hz
- Max. AC Current Draw: 120 VAC, 2 Amps; 230 VAC, 1 Amp (max. computed with all programs running and optional accessories installed)
- Transformer output: 24 VAC, 4 A, at 120 VAC
 - Decoder Line (path) output: 34 V peak-to-peak
 - Decoder Power draw: 40 mA per active output
 - Solenoid capacity: 2 standard 24 VAC Hunter solenoids per output within 100' runs, up to 14 solenoids max. simultaneous
- Wiring, Decoder to solenoid: 150' max.
- 6 two-wire output paths to field decoders
- Diagnostic LEDs with line status, signal activity, decoder and status
- ▶ = *Advanced Feature descriptions on pages 84*



ICD-100, 200, ICD-SEN
Height: 3½"
Width: 1½"
Depth: ¾"

ICD-400, 600
Height: 3½"
Width: 1¾"
Depth: 1½"

ID WIRE MODEL GUIDE

14 AWG Decoder Cable		12 AWG Long Range, Heavy-Duty Decoder Cable	
ID1GRY	Gray jacket	ID2GRY	Gray jacket
ID1PUR	Purple jacket	ID2PUR	Purple jacket
ID1YLW	Yellow jacket	ID2YLW	Yellow jacket
ID1ORG	Orange jacket	ID2ORG	Orange jacket
ID1BLU	Blue jacket	ID2BLU	Blue jacket
ID1TAN	Tan jacket	ID2TAN	Tan jacket

ID WIRE MAXIMUM WIRE RUNS

ID 1 Wire	ID 2 Wire
5,000' with I-Core/DUAL® systems	7,500' with I-Core/DUAL systems
10,000' with ACC/ICD systems	15,000' with ACC/ICD systems

ACC-99D DECODER	
Model	Description
ACC-99D	2-Wire decoder controller with 99-Station capacity, metal cabinet
ACC-99D-SS	2-Wire decoder controller with 99-Station capacity, stainless steel wall mount
ACC-99D-PP	2-Wire decoder controller with 99-Station capacity, plastic pedestal
ACC-PED	Metal pedestal, gray powder-coated, for use with I-Core and ACC metal controllers
PED-SS	Stainless steel pedestal for use with I-Core and ACC stainless controllers

DECODER MODULES	
Model	Description
ICD-100	Single-station decoder with surge suppression and ground wire
ICD-200	2-Station decoder with surge suppression and ground wire
ICD-400	4-Station decoder with surge suppression and ground wire
ICD-600	6-Station decoder with surge suppression and ground wire
ICD-SEN	2-input sensor decoder with surge suppression and ground wire