

ACCESSORIES

DBRY-6

Models

- DBRY100: Bulk 100 connectors (100 tubes loose in box, plus inner box with 100 wire nuts)
- DBRY2X25: 25 x 2-packs (2 tubes and wire nuts in a plastic bag, x 25 units)

Features

- UL Listed for 600 Volts direct burial
- Improved red-and-yellow wire nut, eliminating the need for two different sizes
- A snap-lock feature that secures the wire nut in the bottom of the light blue waterproof tube
- 3 wire exit cutouts in the strain relief cap, to ease wire routing
- Meets Directive 2006/95/EC and IEC standards EN61984:2009, EN60998-1:2004, and EN60998-2-4:2005



Waterproof Wire Connectors

DBRY100, DBRY2X25

HCV

Models

- HC-50F-50F: ½" Female inlet x ½" Female outlet
- HC-50F-50M: ½" Female inlet x ½" Male outlet
- HC-75F-75M: ¾" Female inlet x ¾" Male outlet

Features

- Adjustment access from top of valve
- Adjusts to compensate for elevational changes up to 11 m: Maximum flexibility
- Variety of inlet and outlet options: Reduces need for additional fittings
- Meets schedule 80 specifications: Durable under high pressure

Pressure loss charts for HCV products on page 230



HCV

Overall height: 7.5 cm

HUNTER SPIRAL BARB ELBOWS

Models

- HSBE-050: ½" male x spiral barb elbow
- HSBE-075: ¾" male x spiral barb elbow
- HSBE TOOL: Insert tool

Features

- For use with FLEX_{SG} Tubing
- Acetal material for sharp barbs
- Operating pressure up to 5.5 bar; 550 kPa
- Compatible with FLEX_{SG} and other brands



Spiral Barb Elbows

HSBE-TOOL, HSBE-050, HSBE-075

FLEX_{SG} TUBING

Models

- FLEX_{SG}: 30 m roll
- FLEX_{SG}-18: 45 cm pre-cut lengths

Features

- Engineered to resist kinking
- Inside diameter: 1.2 cm
- Operating pressure: up to 5.5 bar; 550 kPa
- Linear low-density polyethylene material



FLEX_{SG} Tubing

30 m and 45 cm pre-cut lengths

ACCESSORIES

SJ SWING JOINTS

Models

- SJ-506: ½" threaded x 15 cm length
- SJ-7506: ½" x ¾" threaded x 15 cm length
- SJ-706: ¾" threaded x 15 cm length
- SJ-512: ½" threaded x 30 cm length
- SJ-7512: ½" x ¾" threaded x 30 cm length
- SJ-712: ¾" threaded x 30 cm length

Features

- Unique leak-free swivel ells on both ends can be installed in any position for maximum versatility
- Pressure rated to 10 bar; 1000 kPa

Pressure loss charts for SJ products on page 230

SPOTSHOT HOSE-END NOZZLE

Models

- ¾" Hose thread inlet – P/N 160700
- 1" (25 mm) Hose thread inlet – P/N 160705

Features

- Variable nozzle stream choices:
- Fan – Broad light stream for turf hot spots
- Soak – Medium stream for dust control areas
- Jet – Tight focused stream for power washing

Operating Specifications

- Flow – 132 l/min; 8 m³/hr at 5.5 bar; 551 kPa*

* Not recommended for residential use with regulated, low pressure or low flow conditions.



SJ Swing Joint
15 cm or 30 cm links



SpotShot Hose-End Nozzle
¾" P/N 160700
1" (25 mm) P/N 160705