

ACCU SYNC®

Gain unparalleled pressure regulation for any Hunter valve.

OPERATING SPECIFICATIONS

- Regulation from 20 to 100 PSI
- Static pressure: 150 PSI
- Required dynamic pressure differential: 15 PSI
- Works with AC- and DC-latching solenoids
- Works with any Hunter valve
- Warranty period: 2 years

ACCU SYNC VALVE RECOMMENDED FLOW RANGE

Valve	Flow GPM
PGV-100/101	5-40
PGV-151	20-120
PGV-201	40-150
ICV-101	5-40
ICV-151	20-150
ICV-201	40-200
ICV-301	150-300
IBV-101	5-40
IBV-151	20-150
IBV-201	40-200
IBV-301	150-300

ACCU SYNC APPLICATIONS

- **Adjustable 20-100 PSI** For full customization, the adjustable Accu Sync can regulate pressure from 20 to 100 PSI
- **Fixed 30 PSI** Ideal for spray systems
- **Fixed 40 PSI** Ideal for MP Rotator® nozzles and large in-line drip systems

ADJUSTABLE



AS-ADJ

Height with solenoid: 3/4"

ADAPTER



SOLENOID ADAPTER

FIXED



AS-30

Height with solenoid: 3/4"



AS-40

Height with solenoid: 3/4"



Installation

Accu Sync shown installed on ICV and PGV valves