

# DISTRIBUTION TUBING

Add stability and flexibility when using point-source emitters or micro sprays.

## KEY BENEFITS

- High quality vinyl or polyethylene securely connects to acetal ¼" fittings
- Vinyl is more flexible, but it softens in high heat and should be used in cooler climates
- Polyethylene performs well in warmer climates

## PRODUCT SPECIFICATIONS

- Material: polyethylene or vinyl
- Coil sizes: 100', 250', and 1,000'

## OPERATING SPECIFICATIONS

- Operating pressure range: up to 60 PSI
- Warranty period: 2 years



¼" Tubing

¼" TUBING - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1	Model	2	Tubing Diameter	3	Length
	HQPE = Polyethylene tubing		250 = 0.250" outside diameter		100 = 100'
	HQV = Vinyl tubing				250 = 250'
					1K = 1,000'

Example:

HQPE-250-1K = ¼" polyethylene tubing in a 1,000' roll

# ¼" BARBED FITTINGS

Ensure a superior hold with robust acetal construction.

## KEY BENEFITS

- Acetal material provides a secure connection
- Goof plug lays flat to help prevent leaking

## PRODUCT SPECIFICATIONS

- Fits Hunter MLD and distribution tubings

## OPERATING SPECIFICATIONS

- Pressure range: up to 60 PSI
- Warranty period: 1 year



QB-TEE  
¼" barb tee



QB-ELB  
¼" barb elbow



QB-CPL  
¼" barb coupling



QB-CRS  
¼" barb cross



GP-025  
Goof plug

### ¼" Barb Fittings:

Use with MLD or any vinyl or polyethylene ¼" tubing, UV-stabilized materials, and durable single barb connection.