

ECO-WRAP™

Irrigate more efficiently than blank dripline with fleece-wrapped dripline.

KEY BENEFITS

- Perfect for narrow areas that are difficult to irrigate with standard methods
- Anti-siphon feature and fleece wrap protect against debris and root intrusion
- Saves 20-40% more water than standard products due to superior capillary movement of water to the entire root zone, promoting healthier root growth
- Non-draining, pressure-compensating emitters open/close simultaneously, maximising efficiency
- Check height of 1.5 m minimises system drainage and runoff

PRODUCT SPECIFICATIONS

- Flow rate: 2.1 l/hr
- Emitter spacing: 30 cm
- Tubing dimensions: 0.660" x 0.560" (outside/inside diameter)
- Roll length: 16 mm = 100 m; 17 mm = 90 m
- Accepts 16 mm barb or LOC fittings

OPERATING SPECIFICATIONS

- Operating range: 1.0 to 3.5 bar; 100 to 350 kPa
- Minimum filtration: 120 mesh; 125 microns
- Air relief recommended for sloping conditions greater than 1.5 m
- Recommended installation depth: turf (10-16 cm); other (10-30 cm)
- Compatible with Eco-Mat
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)

MAXIMUM RUN LENGTH FOR ECO-MAT AND ECO-WRAP

Pressure (bar; kPa)	Length (m)
1.0; 100	52
1.5; 150	75
2.0; 200	95
2.5; 250	106
3.5; 350	126
4.0; 400	130



Eco-Wrap


ECO-WRAP

Model	Description
ECO-WRAP-16	PLD (16 mm) fleece drip wrap, 100 m roll
ECO-WRAP-17	HDL (17 mm) fleece drip wrap, 90 m roll

Eco-Wrap Installed



Compatible with:



Soil-Clik
Page 151



Eco-Indicator
Page 173