

ECO-WRAP®

Subsurface Irrigation: **Under Turf, Gardens, Shrubs, Trees**

FEATURES

- High distribution uniformity surpassed only by the Eco-Mat
- Promotes healthier plant roots
- Eliminates overspray onto sidewalks, buildings, or vehicles
- Ideal for difficult areas between flagstone and pavers
- Use with PLD-Loc or barbed PLD fittings
- Fleece-wrapped professional landscape dripline
- Transports water faster and more efficiently than bare dripline
- Pressure-compensating
- Check valves keep the line charged up to 1.5 m and prevent low point drainage
- Fleece fully moistens in less than 3 minutes allowing far better uniformity than bare dripline
- Recommended for use with all Hunter Drip Control Zone Kits
- Warranty period: 5 years (2 additional years for environmental stress cracking)



Eco-Wrap

OPERATING SPECIFICATIONS

- Minimum filtration 120 mesh; 125 microns
- Operating pressure range: 1.0 to 3.5 bar; 100 to 350 kPa
- Compatible with 16 mm and 17 mm insert barb fittings

ECO-WRAP TECHNICAL SPECIFICATIONS

	16 MM	17 MM
Flow	2.2 l/hr; 0.13 m ³ /hr	2.2 l/hr; 0.13 m ³ /hr
Roll Length	100 m	76 m
Operating Pressure	1.0 to 3.5 bar; 100 to 350 kPa	1.0 to 3.5 bar; 100 to 350 kPa
Minimum Filtration	120 mesh; 125 microns	120 mesh; 125 microns
Emitter Spacing	30 cm	30 cm

Eco-Wrap Installed

