

FLOW-CLITM

Sensor: **Flow**

Add high-flow shutoff capabilities to any irrigation controller with this simple, adjustable device.

KEY BENEFITS

- Automatically shuts down entire system if an overflow condition occurs, helping to protect against flood damage and erosion
- Single-button calibration to set highest flow rate
- User-adjustable timing and delay for sensor response
- Compatible with all Hunter AC-powered controllers for a variety of applications
- Multi-colour LED indicates system status and if flow is within limits

OPERATING SPECIFICATIONS

- Recommended pressure range: 1.5 to 15.0 bar; 150 to 1500 kPa
- Current draw (24 VAC): 0.025 A
- Switching current: 2 A maximum
- Sensor wiring: 2 x direct burial, 0.75 mm² or greater, colour-coded or marked for polarity, up to 300 m from the interface module
- Programmable start up delay: 0 to 300 seconds (allows for system hydraulics to stabilise and prevents false flow readings)
- Programmable interrupt period: 5 to 60 minutes (or option to reset manually)
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- FCT fittings for 25 mm to 100 mm pipe diameters



Flow-Click Sensor and Module shown with required FCT fitting for pipe installation (sold separately)

Compatible with:



Waterproof Wire Connector

SENSORS

FLOW-CLI ^K	
Model	Description
FLOW-CLI ^K	Standard kit for all 24 VAC controllers. Includes sensor and interface module, sensor requires FCT for pipe installation.
REQUIRED USER-INSTALLED OPTION (SPECIFY SEPARATELY)	
Model	Description
FCT-100	1" (25 mm) Schedule 40 sensor receptacle tee
FCT-150	1½" (40 mm) Schedule 40 sensor receptacle tee
FCT-158	1½" (40 mm) Schedule 80 sensor receptacle tee
FCT-200	2" (50 mm) Schedule 40 sensor receptacle tee
FCT-208	2" (50 mm) Schedule 80 sensor receptacle tee
FCT-300	3" (80 mm) Schedule 40 sensor receptacle tee
FCT-308	3" (80 mm) Schedule 80 sensor receptacle tee
FCT-400	4" (100 mm) Schedule 40 sensor receptacle tee

BSP ADAPTERS FOR FCT FITTINGS	
Diameter	Model
1" (25 mm)	795700
1½" (40 mm)	795800
2" (50 mm)	241400
3" (80 mm)	477800

FLOW RANGE				
Pipe Diameter	Operating Range			
	Minimum l/min	Minimum m ³ /hr	Suggested Maximum* l/min	Suggested Maximum* m ³ /hr
1" (25 mm)	7.6	0.45	64	3.84
1½" (40 mm)	19	1.14	132	8.0
2" (50 mm)	37.8	2.26	208	12.5
3" (80 mm)	106	6.36	450	27.0
4" (100 mm)	129	7.74	750	45.0

Notes:

* Good design practice dictates the maximum velocity not to exceed 1.5 m/sec. Suggested maximum velocity is based upon Class 200 IPS plastic pipe.