

FLOW-CLI[®]

Add high-flow shutoff capabilities to any irrigation controller with this simple, adjustable device.

KEY BENEFITS

- Automatically shuts down entire system if an overflow condition occurs, helping to protect against flood damage and erosion
- Single-button calibration to set highest flow rate
- User-adjustable timing and delay for sensor response
- Compatible with all Hunter AC-powered controllers for a variety of applications
- Multi-color LED indicates system status and if flow is within limits

OPERATING SPECIFICATIONS

- Recommended pressure range: 0 to 220 PSI
- Current draw (24 VAC): 0.025 A
- Switching current: 2 A maximum
- Sensor wiring: 2 x direct burial, 18 AWG or greater, color-coded or marked for polarity, up to 1,000' from the interface module
- Programmable start up delay: 0 to 300 seconds (allows for system hydraulics to stabilize and prevents false flow readings)
- Programmable interrupt period: 5 to 60 minutes (or option to reset manually)
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- FCT fittings for 1" to 4" pipe diameters

Sensor: **Flow**



Flow-Click sensor and module shown with required FCT fitting for pipe installation (sold separately)

FLOW-CLI[®]

Model	Description
FLOW-CLI [®]	Standard kit for all 24 VAC controllers. Includes sensor and interface module, sensor requires FCT for pipe installation.

REQUIRED USER-INSTALLED OPTION (SPECIFY SEPARATELY)

Model	Description
FCT-100	1" Schedule 40 sensor receptacle tee
FCT-150	1½" Schedule 40 sensor receptacle tee
FCT-158	1½" Schedule 80 sensor receptacle tee
FCT-200	2" Schedule 40 sensor receptacle tee
FCT-208	2" Schedule 80 sensor receptacle tee
FCT-300	3" Schedule 40 sensor receptacle tee
FCT-308	3" Schedule 80 sensor receptacle tee
FCT-400	4" Schedule 40 sensor receptacle tee

FLOW RANGE

Pipe Diameter	Operating Range (GPM)	
	Minimum	Suggested Maximum*
1"	2	17
1½"	5	35
2"	10	55
3"	28	120
4"	34	200

Note:

*Good design practice dictates the maximum flow not to exceed 5/sec. Suggested maximum flow is based upon Class 200 IPS plastic pipe.