

IH RISERS

Simplify point-to-point irrigation with vandal-resistant, heavy-duty IH Risers.

KEY BENEFITS

- Heavy-duty, military-grade, vandal-resistant design
- Made of flexible PVC for durability
- Brown components blend in with landscape
- Accepts any 1/2" FPT emitter
- Ideal for slopes
- Pre-assembly reduces labour by up to 50%
- At-grade or below-grade installation
- Available in multiple lengths for easy assembly
- Pre-assembled with 1/2" MPT adapter and specified emitter with check valve
- Available as components for custom assemblies
- Check valve holds back 3.6 m of head

OPERATING SPECIFICATIONS

- Maximum flow: 26.5 l/min
- Maximum pressure: 4.1 bar; 410 kPa
- Warranty period: 2 years



IH RISERS



SCREEN-CV

Filter screen with 3.6 m check valve



IH-FIT-3850

3/8" x 1/2" MPT IH fitting



IH-FIT-3850-R

3/8" x 1/2" MPT IH fitting (reclaimed)



IPS-050-250



IH-250

Flexible PVC for creating headers or custom risers

IH RISER COMPONENTS SOLD SEPARATELY

| Model | Description |
|---------------|--|
| SCREEN-CV | Filter screen with 2.7 m check valve |
| IH-FIT-3850 | 3/8" x 1/2" MPT IH fitting |
| IH-FIT-3850-R | 3/8" x 1/2" MPT IH fitting (reclaimed) |
| IH-250 | 75 m length of irrigation hose |
| IPS-050-250 | 75 m length of 1/2" IPS |

IH Risers with Emitters - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

| 1 Riser Length | 2 Flow with Check Valve Screen | 3 Fitting Options |
|---------------------|--------------------------------|--------------------------------|
| IH-06 = 15 cm riser | 05-CV = 2 l/hr | (blank) = Brown |
| IH-12 = 30 cm riser | 10-CV = 4 l/hr | R = Reclaimed (purple fitting) |
| IH-18 = 45 cm riser | 20-CV = 8 l/hr | |
| IH-24 = 60 cm riser | 40-CV = 15 l/hr | |
| IH-36 = 90 cm riser | 60-CV = 23 l/hr | |

Example:

IH-12-10-CV = 30 cm irrigation hose riser with 4 l/hr emitter with brown fittings