

LOC FITTINGS

LOC fittings are compatible with any nominal 1/2" tubing and dripline for quicker installs and easier repairs.

KEY BENEFITS

- Glass-filled polypropylene for added durability
- Thread lock connection method provides a secure connection while still allowing flexibility for service and system changes

PRODUCT SPECIFICATIONS

- Use with PLD, HDL, or other 16–18 mm dripline
- Install with PLD-IAC/PLD-IAE grommet and a 17.5 mm spade drill bit

OPERATING SPECIFICATIONS

- Operating pressure range: up to 10 bar; 1,000 kPa
- Warranty period: 2 years



PLD-LOC 075
3/4" male pipe thread x LOC



PLD-LOC 050
1/2" male pipe thread x LOC



PLD-LOC CAP
End cap x LOC



PLD-LOC ELB
Locking elbow



PLD-LOC CPL
Locking coupler



PLD-LOC FHS
3/4" female hose swivel x LOC



PLD-LOC TEE
Locking tee

17 MM BARB FITTINGS

Acetal construction holds vinyl and PE tubing for an ideal low-cost choice when installing dripline.

KEY BENEFITS

- Acetal material provides a secure connection
- Dual barb removes the need for clamps

PRODUCT SPECIFICATIONS

- Use with HDL or other 17 mm dripline
- Install with PLD-IAC/PLD-IAE grommet and a 17.5 mm spade drill bit

OPERATING SPECIFICATIONS

- Operating pressure range: up to 7 bar; 700 kPa
- Warranty period: 1 year



PLD-050
1/2" MPT x 17 mm barb



PLD-ELB
17 mm barb elbow



PLD-075
3/4" MPT x 17 mm barb



PLD-CPL
17 mm barb coupling



PLD-CAP
17 mm barb x 1/2" MPT with cap



PLD-075-TB-TEE
17 mm barb tee x 3/4" thread



PLD-BV
17 mm barb shut-off valve



PLD-TEE
17 mm barb tee



PLD-075-TB-ELB
3/4" FPT x 17 mm barb elbow



PLD-050-TB-TEE
1/2" FPT x 17 mm barb tee



PLD-IAC
(with grommet)
Insert adapter x 17 mm coupling



PLD-IAE
(with grommet)
Insert adapter x 17 mm elbow



PLD-CRS
17mm barb cross