

MLD

Use this 6 mm dripline solution for tight spaces and raised planters.

KEY BENEFITS

- Superior flexibility makes MLD an excellent choice for small spaces and raised containers
- Properly irrigates without being intrusive to the landscape

PRODUCT SPECIFICATIONS

- Colours: brown or black polyethylene
- Emitter spacing: 15 cm or 30 cm
- Coil sizes: 30 m or 75 m
- 6.4 mm x 4.5 mm (outside/inside diameters)
- Use with 6 mm barb fittings

OPERATING SPECIFICATIONS

- Pressure range: 0.7 to 2.8 bar; 70 to 280 kPa
- Minimum filtration: 150 mesh; 120 microns
- Maximum run lengths: 15 cm = 4.6 m; 30 cm = 9.2 m
- Warranty period: 2 years



MLD

MLD Installed



MLD - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Spacing	3 Length	4 Options
MLD-05	06 = 15 cm 12 = 30 cm	100 = 30 m 250 = 75 m	BL = Black (blank) = Brown

Example: MLD-05 - 12 - 250 = 1.9 l/hr mini dripline with 30 cm spacing in a 76 m roll, brown

MLD FLOW CHART

