

MINI-CLI[®]

Sensor: **Rain**

This sensor halts scheduled irrigation when it detects a preset level of rain has fallen to stop water waste.

KEY BENEFITS

- Shuts off sprinkler system automatically when it rains
- Adjustable from 1/8" to 3/4" of rainfall
- Debris tolerant for reliable operation
- Mountable to gutters using (P/N SGM)
- Stainless steel guard with Mini-Clik sensor for commercial applications (P/N SG-MC)
- Compatible with most irrigation controllers

OPERATING SPECIFICATIONS

- Switch rating (24 VAC): 5 A
- Includes 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

MINI-CLI [®]	
Model	Description
MINI-CLI [®]	Wired rain sensor
MINI-CLI [®] -NO	Wired rain sensor with normally open switch
SG-MC	Stainless steel sensor guard with Mini-Clik sensor
SGM	Optional gutter mount

MINI-CLI[®] INSTALLATION



MINI-CLI[®]

Height: 2"
Length: 6"



SG-MC

Stainless steel sensor guard enclosure for Mini-Clik (includes Mini-Clik)
Height: 5 1/2"
Length: 3"
Width: 4"



SGM

Optional gutter mount
Height: 1/2"
Length: 3"