

# NODE

This battery-powered, waterproof controller offers automatic irrigation control for temporary irrigation and sites without electricity.

## KEY BENEFITS

- Number of stations:
  - 1, 2, 4, or 6
- Battery-operated controller for automatic irrigation without AC power
- Battery-life indicator for battery replacement
- Waterproof enclosure seal protects against water ingress
- 3 flexible programs with 4 start times each and up to 6-hour run times
- Suspend irrigation up to 99 days during the off-season
- Easy Retrieve™ memory backs up the full irrigation schedule if ever changed
- Delay Between Stations for slow-closing valves or pump recharge
- Seasonal adjustment for quicker schedule adjustments without changing run times
- Solar panel provides maintenance-free operation
- Mounts to Hunter solenoids, pipes, flat surfaces, or inside the valve box

## OPERATING SPECIFICATIONS

- One or two 9V alkaline batteries or 1800 mAh solar panel with charging cell
- Operates DC-latching solenoids (P/N 458200)
- 100' maximum wire runs, 18 AWG wire only
- Station output: 9-11 VDC
- P/MV output: 9-11 VDC
- Sensor inputs: 1
- Approvals: IP68, UL, cUL, FCC, CE, RCM
- Warranty period: 2 years



**NODE**  
Diameter: 3½"  
Height: 2½"



**SPXCH**  
Solar panel kit (optional)  
Height: 3¼"  
Width: 3"  
Depth: ⅝"

## NODE



Compatible with:



**Mini-Clik  
Sensor**  
Page 135



**Freeze-Clik  
Sensor**  
Page 142

NODE	
Model	Description
NODE-100	Single-station battery controller and DC-latching solenoid
NODE-100-LS	Single-station battery controller
NODE-200	2-station battery controller
NODE-400	4-station battery controller
NODE-600	6-station battery controller
NODE-100-VALVE	Single-station battery controller with PGV-101G valve and DC-latching solenoid (NPT threads)
458200	DC-latching solenoid