

Gain simple and trouble-free operation without the need for a separate backflow preventer.

KEY BENEFITS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Captive bonnet screws eliminate the possibility of lost parts during disassembly
- Triple-tool bonnet screws are compatible with standard or Phillips screwdrivers as well as a nut driver
- Removable anti-siphon cap for simple servicing
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximizes efficiency and prolongs the life of the system

USER-INSTALLED OPTIONS

- Accu Sync® pressure regulation at the valve*
- DC-latching solenoid for battery-powered controllers

FACTORY-INSTALLED OPTIONS

- LS: Valve without solenoid
- DC: DC-latching solenoid for battery-powered controllers

OPERATING SPECIFICATIONS

- Flow: 0.2 to 40 GPM
- Recommended pressure range: 20 to 150 PSI
- Temperature rating: 150°F
- Warranty period: 2 years

* Accu Sync product information on **page 83**



PGV-075-ASV

Inlet diameter: 3/4"
Height: 5 1/2"
Length: 5 3/4"
Width: 2 1/2"



PGV-101-ASV

Inlet diameter: 1"
Height: 5 1/2"
Length: 6 1/4"
Width: 2 1/2"

Double-Beaded Diaphragm



PGV-ASV	
Model	Description
PGV-075-ASV	3/4" plastic anti-siphon electric valve, with flow control, NPT inlets
PGV-075-ASV-S	3/4" plastic anti-siphon electric valve, with flow control, slip inlets
PGV-075-ASV-LS	3/4" plastic anti-siphon electric valve, with flow control, NPT inlets, no solenoid
PGV-101-ASV	1" plastic anti-siphon electric valve, with flow control, NPT inlets
PGV-101-ASV-S	1" plastic anti-siphon electric valve, with flow control, slip inlets
PGV-101-ASV-LS	1" plastic anti-siphon electric valve, with flow control, NPT inlets, no solenoid

PGV-ASV PRESSURE LOSS IN PSI		
Flow (GPM)	3/4"	1"
1	1	1
5	2	2
10	2	2
15	3	3
20	6	6
25		6
30		9
35		16
40		20