

PRS40

To optimize MP Rotator performance, the Pro-Spray PRS40 is pressure-regulated to 40 PSI.

KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Pressure-regulated to 40 PSI for the MP Rotator
- Gray cap for easy field identification
- Co-molded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- FloGuard technology option eliminates water waste in the event of a missing nozzle

ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI
- Warranty period: 5 years

FACTORY-INSTALLED OPTIONS

- Check valve available for 4", 6", and 12" models (up to 14' of elevation)
- Reclaimed water identification
- FloGuard technology available for pop-up models

USER-INSTALLED OPTIONS

- Check valve (up to 14' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458562SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps



PROS-00-PRS40
Retracted height: 4½"
Inlet size: ½"



PROS-04-PRS40-CV
Retracted height: 5⅞"
Pop-up height: 4"
Exposed diameter: 2¼"
Inlet size: ½"



FloGuard Technology

PROS-06-PRS40-CV
Retracted height: 8¾"
Pop-up height: 6"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-12-PRS40-CV
Retracted height: 16⅞"
Pop-up height: 12"
Exposed diameter: 2¼"
Inlet size: ½"

PRO-SPRAY PRS40 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Feature Options	3 Specialty Options
PROS-00-PRS40 = 40 PSI regulated shrub adapter PROS-04-PRS40 = 40 PSI regulated 4" pop-up PROS-06-PRS40 = 40 PSI regulated 6" pop-up PROS-12-PRS40 = 40 PSI regulated 12" pop-up	(blank) = No option CV = Factory-installed drain check valve <i>(Pop-up models only)</i>	(blank) = No option R = Factory-installed reclaimed body cap F = FloGuard technology F-R = FloGuard technology with reclaimed body cap

PRO-SPRAY PRS40 (SIDE INLET) MODELS

Model

PROS-06-SI-PRS40 = 40 PSI regulated 6" pop-up with side inlet

PROS-12-SI-PRS40 = 40 PSI regulated 12" pop-up with side inlet

Examples:

PROS-06-SI-PRS40 = 6" pop-up with side inlet regulated at 40 PSI
PROS-06-PRS40-CV = 6" pop-up regulated at 40 PSI, drain check valve
PROS-12-PRS40-CV-F-R = 12" pop-up regulated at 40 PSI, drain check valve, and FloGuard technology with reclaimed body cap

Compatible with:



MP Rotator