

# POINT-SOURCE EMITTERS

Ensure accurate irrigation for mixed and sparse plantings with a wide range of flow rates.

## KEY BENEFITS

- Pressure-compensating for consistent and reliable flow
- Colour-coded by flow for easy identification in the field
- Earth-tone colours blend in well with the surrounding environment
- Three inlet variations: 6 mm barb, 10-32 thread, ½" FPT
- Coined edges for easy grip
- Self-piercing barb
- Optional diffuser cap
- Self-flushing diaphragm

## OPERATING SPECIFICATIONS

- Recommended pressure range: 1.4 to 3.5 bar; 140 to 350 kPa
- Minimum filtration: 150 mesh; 100 microns
- Warranty period: 2 years

### ½" FEMALE THREAD (BROWN BASE)

	Model	Inlet Type	Flow (l/hr)
● Blue	HEB-05-BR	½" female thread	2.0
● Red	HEB-20-BR	½" female thread	8.0
● Tan	HEB-40-BR	½" female thread	15.0
● Orange	HEB-60-BR	½" female thread	23.0



**Pocket Punch**  
P/N POCKETPUNCH  
(Punches, inserts, and removes emitters)



**Hunter Emitter Multi-Tool**  
P/N HEMT  
(Punches pilot holes and pellets, inserts and removes emitters, cuts tubing)

### EMITTER MODEL CHART

	Model	Inlet Type	Flow (l/hr)
● Blue	HE-050-B	Self-piercing barb	2.0
● Black	HE-10-B	Self-piercing barb	4.0
● Red	HE-20-B	Self-piercing barb	8.0
● Tan	HE-40-B	Self-piercing barb	15.0
● Orange	HE-60-B	Self-piercing barb	23.0
● Blue	HE-050-T	10-32 thread	2.0
● Black	HE-10-T	10-32 thread	4.0
● Red	HE-20-T	10-32 thread	8.0
● Tan	HE-40-T	10-32 thread	15.0
● Orange	HE-60-T	10-32 thread	23.0
● Blue	HEB-05	½" female thread	2.0
● Black	HEB-10	½" female thread	4.0
● Red	HEB-20	½" female thread	8.0
● Tan	HEB-40	½" female thread	15.0
● Orange	HEB-60	½" female thread	23.0

### DIFFUSER CAP

(HE-DIFF)  
Gently diffuses water on higher flow emitters to prevent erosion.



### ½" FEMALE THREAD (brown base)



### Inlet Options



① Self-piercing barb



② 10-32 thread



③ ½" female thread