PRO-HC

Use this rugged, cost-effective, professional-grade Wi-Fi controller for residential and light commercial applications. Try Hydrawise Software today at hydrawise.com.

KEY BENEFITS

- Number of stations:
 6, 12, or 24 (fixed models)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 2 sensor inputs available for use with any Clik Sensor and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrawise™ Software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal (only) TLS, SSL
- Approvals: IP44 (outdoor), UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 2 years


USER-INSTALLED OPTIONS

• Wireless HC Flow Meter option permits wireless flow monitoring for Hydrawise-enabled systems



Pro-HC (indoor/outdoor) Height: 22.8 cm Width: 25 cm Depth: 10 cm

Compatible with:



PRO-HC - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 2 3 1 Model Transformer Options **00** = 120 VAC **PHC-6** = 6-station controller (blank) = No option 01 = 230 VAC E = 230 VAC with European cable PHC-12 = 12-station controller and plug PHC-24 = 24-station controller A = 230 VAC with Australian cable and plug

Example:

PHC-2400 = 24-station, plastic wall mount cabinet, 120 VAC with U.S. cable and plug PHC-1201-E = 12-station, plastic wall mount cabinet, 230 VAC with European cable and plug



Smart WaterMark

Recognised as a responsible water-saving tool

