

PRO-HC

Use this rugged, professional-grade Wi-Fi controller for residential and light commercial applications.

KEY BENEFITS

- Number of stations:
 - 6, 12, or 24
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 2 sensor inputs available for use with any Clik sensor and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrowise software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: Plastic IP44, UL, cUL, FCC, CE, RCM
- Warranty period: 2 years



Pro-HC
(plastic indoor)
Height: 21 cm
Width: 24 cm
Depth: 8.8 cm




Pro-HC
(plastic outdoor)
Height: 22.8 cm
Width: 25 cm
Depth: 10 cm

PRO-HC - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Transformer	3 Indoor/Outdoor	4 Options
PHC-6 = 6-station controller PHC-12 = 12-station controller PHC-24 = 24-station controller	00 = 120 VAC 01 = 230 VAC	(blank) = Outdoor model (internal transformer) i = Indoor model (plug-in transformer)	(blank) = No option E = 230 VAC with European connections A = 230 VAC with Australian connections (outdoor model has internal transformer with cord)

Example:
PHC-2400 = 24-station, 120 VAC, outdoor plastic controller


Compatible with:



HC Flow Meter
Page 147



Rain-Clik Sensor
Page 144



Soil-Clik Sensor
Page 151



Smart WaterMark
Recognised as a responsible water-saving tool