

PRO-HC

Use this rugged, professional-grade Wi-Fi controller for residential and light commercial applications.

KEY BENEFITS

- Number of stations:
 - 6, 12, or 24
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 2 sensor inputs available for use with any Clik sensor and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrowise software
- 2 $\frac{3}{4}$ " full-color touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: Plastic IP44 (outdoor), UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

PRO-HC	
Model	Description
PHC-600i	Fixed 6-station, plastic indoor wall mount
PHC-600	Fixed 6-station, plastic outdoor wall mount
PHC-1200i	Fixed 12-station, plastic indoor wall mount
PHC-1200	Fixed 12-station, plastic outdoor wall mount
PHC-2400i	Fixed 24-station, plastic indoor wall mount
PHC-2400	Fixed 24-station, plastic outdoor wall mount




Pro-HC
(plastic indoor)
Height: 8 $\frac{1}{4}$ "
Width: 9 $\frac{1}{2}$ "
Depth: 3 $\frac{1}{2}$ "



Pro-HC
(plastic outdoor)
Height: 9"
Width: 10"
Depth: 4"

Compatible with:



HC Flow Meter
Page 137



Rain-Clik Sensor
Page 134



PXS SYNC Accessory
Visit fxl.com



EPA WaterSense Approved

Recognized as a responsible water-saving tool by the U.S. Environmental Protection Agency