

# ROAM

Enable convenient controller management from a distance with this handheld wireless remote.

## KEY BENEFITS

- Compatibility with Hunter X-Core™, X2™, Pro-C™, HPC, ICC2, HCC, I-Core™, ACC, and ACC2 controllers provides remote operation for projects of any size
- Manually start individual stations or programs for quick maintenance checks and troubleshooting
- 128 programmable addresses available prevents cross-communication between multiple remotes within close proximity of each other
- Programmable run times from 1 to 90 minutes, which will not overwrite regular automatic programming
- Manual operation up to 240 stations provides flexibility for larger projects

## OPERATING SPECIFICATIONS

- Range: 300 m from transmitter to receiver
- Transmitter power source: 4 x AAA batteries included
- Receiver power source: 24 VAC, 0.010 A
- System operating frequency: 433 MHz
- SmartPort™ installation: Maximum 15 m from controller
- FCC and CE approved for use in the United States and internationally
- Warranty period: 2 years



### Transmitter and Receiver

Height: 18 cm  
Width: 6 cm  
Depth: 3 cm



### SmartPort

Hunter remotes require the installation of a SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.



### Wall-Mount Bracket for SmartPort

P/N 258200

ROAM	
Model	Description
ROAM-KIT	Transmitter, receiver, SmartPort wiring harness, and 4 AAA batteries included
ROAM-R	Receiver unit
ROAM-TR	Transmitter unit and 4 AAA batteries included

OPTIONS	
Model	Description
ROAM-WH	SmartPort wiring harness (length: 1.8 m)
ROAM-SCWH	Shielded SmartPort wiring harness (length: 7.6 m)
258200	Wall-mount bracket for SmartPort