RAIN-CLIK®

To prevent water waste, built-in Quick Response® Technology instantly shuts down irrigation as soon as it starts raining.

KEY BENEFITS

- · Quick Response Technology triggers instant rain shutoff
- Freeze sensing model halts system operation at 37°F
- · Wireless sensor kit simplifies installation
- · Maintenance-free design with integrated battery for wireless models
- · Adjustable vent ring allows for shorter or longer reset period
- Includes gutter bracket and wall mount with wireless models
- · Compatible with most normally open or normally closed irrigation controllers

OPERATING SPECIFICATIONS

- · Quick Response Technology:
 - Time to turn off irrigation system: approximately 2 to 5 minutes for Quick Response
 - Time to reset Quick Response: approximately 4 hours under dry, sunny conditions
 - Time to reset when fully wet: approximately 3 days under dry, sunny conditions
- All models switch rating (24 VAC): 3 A
- Wired models include 25' of 20 AWG sheathed, UL-approved wire
- Wireless model operating frequency: 433 MHz
- Wireless model range is 800' line of sight from sensor to receiver
- Multiple wireless receivers can be operated from a single wireless sensor
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

OPERATING SPECIFICATIONS

- Optional Gutter Mount for wired models (included with WR-CLIK and WRF-CLIK)
- Vandal-resistant Wireless Sensor Guard for flat surfaces or pole mounting (order sensor separately)
- Vandal-resistant Wireless Receiver Guard for pedestal mounting (order receiver separately)





(with mounting arm) Height: 2½" Length: 7" Width: 1"



SGM

optional gutter mount Height: ½"

Length: 3" Width: 1¼"



Wireless Rain-Clik Sensor

(with mounting arm) Height: 3" Length: 8" Width: 1"



Wireless Receiver

(with wall mounting hardware) Height: 3¼" Length: 4" Width: 1½"



Wireless Sensor Guard

(with mounting hardware) Height: 2¾" Length: 3¾" Width: 1¼"



Wireless Receiver Guard

(with mounting hardware) Height: 5" Length: 4" Width: 1¼"

Compatible with:



Waterproof Wire Connector

