

SRM

The SRM is an economical short-range rotor that offers a convenient and efficient alternative to spray heads.

Radius: **4.0 to 9.4 m**
Flow: **0.08 to 0.82 m³/hr; 1.4 to 13.7 l/min**

ROTORS

KEY BENEFITS


- Adjustable arc from 40° to 360° to keep water in the appropriate areas
- Standard factory-installed 2.0 nozzle speeds installation
- QuickCheck™ arc mechanism for fast arc adjustment

OPERATING SPECIFICATIONS

- Nozzle choices: 6
- Radius: 4.0 to 9.4 m
- Flow: 0.08 to 0.82 m³/hr; 1.4 to 13.7 l/min
- Recommended pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Operating pressure range: 1.4 to 7.0 bar; 140 to 700 kPa
- Precipitation rate: 11 mm/hr approximately
- Nozzle trajectory: 14° approximately
- Warranty period: 2 years

USER-INSTALLED OPTIONS

- Drain check valve (up to 2.1 m of elevation) (P/N 462078SP)

SRM		SRM NOZZLES
Model	Description	
SRM-04	10 cm pop-up, adjustable arc, 6 standard nozzles	



SRM-04

Overall height: 18 cm
Pop-up height: 10 cm
Exposed diameter: 3 cm
Inlet size: ½"

SRM



Compatible with:



SJ Swing Joints
Page 68



Hunter FlexSG
Page 68

SRM GREEN NOZZLE PERFORMANCE DATA

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
.50 ● Dk. Green	1.7	170	4.0	0.08	1.4	11	12
	2.0	200	4.3	0.09	1.6	10	12
	2.5	250	4.3	0.11	1.8	12	14
	3.0	300	4.6	0.12	2.0	12	13
	3.5	350	4.6	0.13	2.2	13	15
	3.8	380	4.9	0.14	2.3	12	14
.75 ● Dk. Green	1.7	170	4.9	0.13	2.2	11	13
	2.0	200	5.2	0.14	2.4	11	12
	2.5	250	5.2	0.16	2.7	12	14
	3.0	300	5.5	0.18	3.0	12	14
	3.5	350	5.5	0.19	3.2	13	15
	3.8	380	5.8	0.20	3.4	12	14
1.0 ● Dk. Green	1.7	170	5.8	0.18	2.9	11	12
	2.0	200	6.1	0.19	3.2	10	12
	2.5	250	6.1	0.21	3.5	11	13
	3.0	300	6.4	0.24	3.9	12	13
	3.5	350	6.4	0.25	4.2	12	14
	3.8	380	6.7	0.26	4.4	12	14
1.5 ● Dk. Green	1.7	170	6.7	0.27	4.5	12	14
	2.0	200	7.0	0.29	4.8	12	14
	2.5	250	7.0	0.32	5.4	13	15
	3.0	300	7.3	0.36	6.0	13	16
	3.5	350	7.3	0.39	6.5	15	17
	3.8	380	7.6	0.40	6.7	14	16
2.0 ● Dk. Green	1.7	170	7.3	0.35	5.8	13	15
	2.0	200	7.9	0.38	6.3	12	14
	2.5	250	7.9	0.43	7.1	14	16
	3.0	300	8.2	0.48	8.0	14	16
	3.5	350	8.2	0.53	8.8	16	18
	3.8	380	8.5	0.55	9.2	15	17
3.0 ● Dk. Green	1.7	170	8.2	0.51	8.5	15	17
	2.0	200	8.5	0.56	9.3	15	18
	2.5	250	8.5	0.64	10.6	17	20
	3.0	300	9.1	0.72	12.0	17	20
	3.5	350	9.1	0.78	13.1	19	22
	3.8	380	9.4	0.82	13.7	18	21

Note:

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.