

SOLAR SYNC®

This sensor automatically adjusts controller run times daily based on local climate conditions to reduce water usage and improve plant health.

KEY BENEFITS

- Automatically adjusts irrigation duration based on weather conditions using on-site solar radiation and air temperature
- Quick Response® instant rain shutoff and freeze shutoff at 37°F
- Maintenance-free design with integrated battery for wireless models
- Adjustable vent ring allows for shorter or longer reset period
- Rugged polycarbonate housing and metal extension arm
- Includes gutter bracket and wall mount with wireless models
- Use with Hunter standard controllers, Centralus™ with ICC2 or ACC2, and IMMS™ online central control installations

OPERATING SPECIFICATIONS

- Solar Sync:
 - Adjusts run times daily 3 minutes before midnight using the last 3 days of ET (evapotranspiration) data
- Quick Response:
 - Time to turn off irrigation system: approximately 2 to 5 minutes for Quick Response
 - Time to reset Quick Response: approximately 4 hours under dry, sunny conditions
 - Time to reset when fully wet: approximately 3 days under dry, sunny conditions
- All models switch rating (24 VAC): 3 A
- Wired models include 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Wireless model operating frequency: 433 MHz
- Wireless model range is 800' line of sight from sensor to receiver
- Multiple wireless receivers can be operated from a single wireless sensor
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 5 years

SOLAR SYNC	
Model	Description
SOLAR-SYNC-SEN	Solar Sync sensor, wire, and gutter mount
WSS-SEN	Wireless Solar Sync sensor, receiver, and gutter mount
WS-GUARD	Vandal-resistant wireless sensor guard for flat surfaces or pole mounting (order sensor separately)
WR-GUARD	Vandal-resistant wireless receiver guard for pedestal mounting (order receiver separately)

Sensor: **ET, Rain, Freeze**



Wired Solar Sync Sensor

(with mounting arm)

Height: 3"
Width: 8½"
Depth: 1"



Wireless Solar Sync Sensor

Height: 4½"
Width: 8½"
Depth: 1"



Wireless Solar Sync Receiver

(with wall mounting kit)

Height: 5½"
Width: 1½"
Depth: 1½"



Wireless Sensor Guard

(with mounting hardware)

Height: 2¾"
Width: 3¾"
Depth: 1¼"



Wireless Receiver Guard

(with mounting arm)

Height: 5"
Width: 4"
Depth: 1¼"



EPA WaterSense Approved

Recognized as a responsible water-saving tool by the U.S. Environmental Protection Agency