

SOLAR SYNC®

Sensor: **ET/Rain/Freeze**

FEATURES

- Provides automatic daily weather adjustment to program run times
- Wired and wireless models available
- Solar Sync may be used in IMMS central installations
- Rain and freeze shutoff
- Gutter mount bracket included
- Compatible with Hunter X-Core®, Pro-C®, I-Core®, ICC2, ACC, and ACC2 controllers
- Warranty period: 5 years (10 year battery warranty for wireless model)

SPECIFICATIONS

- Maximum distance sensor to module: 200' (wired model) or 800' (wireless model)
- 40' of wire included in kit (wired model)
- Rain and freeze sensor shutdown capability included

APPROVALS

- FCC, CE



Wired Solar Sync Sensor

(w/mounting arm)
Height: 3"
Width: 8.5"
Depth: 1"



Wireless Solar Sync Sensor

(w/mounting arm)
Height: 4.5"
Width: 8.5"
Depth: 1"



Wireless Solar Sync Receiver

(w/ wall mounting kit)
Height: 5.5"
Width: 1.5"
Depth: 1.5"

SOLAR SYNC

Model	Description
SOLAR-SYNC-SEN	Wired Solar Sync for use with ACC, ACC2, I-Core, ICC2, new Pro-C 400/PCC Series, and X-Core controllers. Includes Solar Sync Sensor and wire.
WSS-SEN	Wireless Solar Sync for use with ACC, ACC2, I-Core, ICC2, new Pro-C 400/PCC Series, and X-Core controllers. Includes wireless Solar Sync Sensor and Wireless Receiver.

