

# SPRAY ACCESSORIES

Spray accessories provide flexibility for installation and maintenance of spray systems.

## SJ SWING JOINTS

### Features

- Unique swivel ells on both ends for easy installation in any configuration
- Airtight connection points for long-term reliability
- Pressure loss charts for SJ products on **page 198**

### Models

- SJ-506: ½" threaded x 6" length standard
- SJ-7506: ½" x ¾" threaded x 6" length
- SJ-706: ¾" threaded x 6" length
- SJ-512: ½" threaded x 12" length
- SJ-7512: ½" x ¾" threaded x 12" length
- SJ-712: ¾" threaded x 12" length

### Operating Specifications

- Pressure-rated to 150 PSI
- Warranty period: 2 years



### SJ Swing Joint

6" and 12" links



### Spiral Barb Elbows

P/N HSBE-TOOL, P/N HSBE-050, P/N HSBE-075

## HUNTER SPIRAL BARB ELBOWS

### Features

- Compatible with Flex<sub>SG</sub> and other brands for a customized swing joint
- Acetal material for sharp barbs

### Models

- HSBE-050: ½" male NPT x spiral barb elbow
- HSBE-075: ¾" male NPT x spiral barb elbow
- HSBE TOOL: Insert tool

### Operating Specifications

- Operating pressure: Up to 80 PSI
- Warranty period: 2 years



### FLEX<sub>SG</sub> Tubing

100' and 18" pre-cut lengths  
Inside diameter: 0.49"

## FLEX<sub>SG</sub> TUBING

### Features

- Engineered to resist kinking
- Textured for easy grip
- Linear low-density polyethylene material
- Meets ASTM D2104, D2239, D2737

### Models

- FLEXSG: 100' roll
- FLEXSG-18: 18" pre-cut lengths

### Operating Specifications

- Operating pressure: up to 80 PSI
- Warranty period: 2 years



### Pro-Spray Shutoff Cap

213600SP

## PRO-SPRAY SHUTOFF CAP

### Features

- Caps off the Pro-Spray for maintenance or drip conversions
- Maintains a clean look to the landscape

### Models

- 213600SP

## SHUTOFF NOZZLE

### Features

- Easy shutoff for spray systems
- Allows heads to pop-up for easy visibility
- Use with Pro-Spray and PS Ultra models

### Models

- 916400SP



### Shutoff Nozzle

916400SP