

STREAM NOZZLES

Prevent runoff for slope, groundcover, and shrub applications with the low precipitation rate of these adjustable arc stream nozzles.

KEY BENEFITS

- Low application rate to avoid runoff
- Ideal for slopes, ground cover, and shrub applications
- Multiple streams provide even coverage
- Adjustable arc from 25° to 360° for design flexibility

OPERATING SPECIFICATIONS




- Recommended operating pressure: 30 PSI
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 30 PSI
- Warranty period: 2 years






S-8A
7' to 9'



S-16A
15' to 18'

MODEL S-8A STREAM SPRAY NOZZLE PERFORMANCE DATA						
Arc	Pressure	Radius	Flow	Precip in/hr		
S-8A	PSI	ft.	GPM	■	▲	
90° 	20	7	0.29	2.28	2.63	
	25	8	0.32	1.93	2.22	
	30	8	0.38	2.11	2.43	
	35	8	0.41	2.29	2.64	
180° 	20	7	0.54	2.12	2.45	
	25	8	0.57	1.71	1.98	
	30	8	0.60	1.80	2.08	
	35	8	0.63	1.89	2.19	
360° 	20	7	1.08	2.12	2.45	
	25	8	1.11	1.67	1.93	
	30	8	1.15	1.73	2.00	
	35	8	1.18	1.77	2.05	
	40	9	1.22	1.45	1.67	

Bold = Recommended pressure

MODEL S-16A STREAM SPRAY NOZZLE PERFORMANCE DATA						
Arc	Pressure	Radius	Flow	Precip in/hr		
S-16A	PSI	ft.	GPM	■	▲	
90° 	20	15	0.40	0.68	0.79	
	25	16	0.46	0.69	0.80	
	30	16	0.50	0.75	0.87	
	35	17	0.54	0.72	0.83	
180° 	20	15	0.67	0.57	0.66	
	25	16	0.80	0.60	0.69	
	30	16	0.88	0.66	0.76	
	35	17	0.97	0.65	0.75	
360° 	20	15	1.19	0.51	0.59	
	25	16	1.46	0.55	0.63	
	30	16	1.66	0.62	0.72	
	35	17	1.82	0.61	0.70	
	40	18	1.99	0.59	0.68	

Bold = Recommended pressure

S-8A

