

SWING JOINTS

BY LASCO FITTINGS, INC.

FEATURES

- Heavy-duty prefabricated PVC swing joints with O-Ring seals
- Available in all popular inlet and outlet configurations
- Choose from 8", 12" or 18" lay arm lengths and Single Top-Out or Triple Top-Out designs
- Unique SnapLok™ outlet with brass threads offers excellent support and durability for quick coupler installations

Swing Joints

- HSJ-0 = Model ¾"
- HSJ-1 = Model 1"
- HSJ-2 = Model 1¼"
- HSJ-3 = Model 1½"



ROTORS

HSJ SWING JOINT - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Inlet Type (from pipe fitting)	3 Outlet Type (to sprinkler inlet)	4 Outlet Style	5 Lay Length
HSJ-0 = ¾" Commercial Swing Joint	2 = Spigot - Short	2 = Male - NPT	2 = Single Top-Out	08 = 8" Lay Arm*
HSJ-1 = 1" Heavy-Duty Swing Joint	3 = Male - NPT	3 = Enlarging - to 1½" Male NPT*	4 = Triple Top-Out*	12 = 12" Lay Arm
HSJ-2 = 1¼" Heavy-Duty Swing Joint	7 = Spigot - 4" Long*	S = Male - 1" Brass NPT SnapLok™ **		18 = 18" Lay Arm
HSJ-3 = 1½" Heavy-Duty Swing Joint	<i>* Not available HSJ-0</i>	T = Male - ¾" Brass NPT/BSP SnapLok™ **	<i>* Not available in S or T Outlet Types</i>	<i>* HSJ-0 only</i>
		<i>* Not available HSJ-0 or HSJ-3</i>		
		<i>** HSJ-1 only - for quick coupler</i>		

Example:

HSJ - 3 - 7 - 2 - 2 - 12 = HSJ 1½" heavy-duty swing joint, 1½" spigot pipe inlet, 1½" Male NPT single top-out outlet, 12" lay arm length.

HIGH-FLOW SWING JOINTS

FEATURES

- Heavy-duty high-flow swing joints with O-ring seals
- HSJ-4 for high-flow I-90 and ST-90 rotors with 1½" inlets
- HSJ-5 for high-flow ST-1600B rotor with 2" inlet
- Available in popular inlet and outlet configurations

High-Flow Swing Joints

- HSJ-4 = Model 2"
- HSJ-5 = Model 3"



HSJ HIGH-FLOW SWING JOINT - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Inlet Type (from pipe fitting)	3 Outlet Type (to sprinkler inlet)	4 Outlet Style	5 Lay Length
HSJ-4 = 2" Heavy-Duty Swing Joint	3 = 2" Male - NPT - Horizontal Side Connection Q = 2" Male - NPT - Vertical Top Connection	7 = 1½" Male - NPT	2 = Single Top-Out	12 = 12" Lay Arm
HSJ-5 = 3" Heavy-Duty Swing Joint	3 = 3" Male - NPT - Horizontal Side Connection V = 3" Male - NPT - Vertical Top Connection	8 = 2" Male - NPT	2 = Single Top-Out	12 = 12" Lay Arm

Example:

HSJ-4-Q7-212 = HSJ 2" heavy-duty swing joint, 2" male NPT vertical top connection to piping, 1½" male NPT outlet to sprinkler, single top-out and 12" lay arm

HSJ-5-38-212 = HSJ 3" heavy-duty swing joint, 3" male NPT horizontal side connection to piping, 2" male NPT outlet to sprinkler, single top-out and 12" lay arm