

ACC2

Number of Stations: **12 to 54**
Type: **Modular**

FEATURES

- Number of stations: 12 to 54
 - Type: Modular
 - Enclosure: Outdoor, metal, stainless steel, and plastic pedestal
 - Independent programs: 32
 - Start times per program: 10
 - Max. station run time: 12 hrs
 - Built-in Solar Sync®
 - Pre-wired with SmartPort®
 - Built-in SD card reader
 - Color backlit display, reversible facepack
 - 8 station block programming groups
 - Warranty period: 5 years
- ▶ Real-time flow monitoring
 - ▶ Flow scheduling/Flow budgeting
 - ▶ Solar Sync Delay/Rain-Delay
 - ▶ Easy Retrieve™ memory
 - ▶ Conditional Response Programming
 - ▶ Password protection with user management
 - ▶ MainSafe™ water source protection
 - ▶ Delay between stations
 - ▶ Calendar days off, by date
 - ▶ Sensor programmability
 - ▶ Cycle and Soak

ELECTRICAL SPECIFICATIONS

- Transformer input: 120/230 VAC
- Power consumption:
 - 120 VAC, Standby: 0.17 A, Typical (6 solenoids): 0.33 A, Max: 1.02 A
 - 230 VAC, Standby: 0.15 A, Typical (6 solenoids): 0.26 A, Max: 0.62 A
- Transformer output: 4.0 A
- Station output: Up to 0.800 A
- P/MV output 3, expandable to 6, 0.800 A
- Sensor inputs: 3 Clik, 3 Flow (expandable to 6), 1 Solar Sync

APPROVALS

- CE, UL, c-UL, RCM, FCC
- Steel: IP44
- Plastic pedestal: IP24

ALL STAINLESS STEEL (SS) MODELS

- Stainless Steel 0.057" gauge steel
 - Passivated for corrosion resistance
- ▶ = *Advanced Feature descriptions on page 88*



Metal Wall Mount (gray or stainless)
Height: 15.7"
Width: 15.7"
Depth: 6.8"



Metal Pedestals
(gray or stainless)
Height: 37"
Width: 15.5"
Depth: 5"



Plastic Pedestal
Height: 39.5"
Width: 23.5"
Depth: 17"



A2M-600
6-station plug-in module with extreme service lightning protection



A2C-F3
3 input flow meter expansion module

ACC2	
Model	Description
A2C-1200-M	12-station base unit controller, expands to 54-stations, gray steel wall mount, outdoor
A2C-1200-SS	12-station base unit controller, expands to 54-stations, stainless steel wall mount, outdoor
A2C-1200-PP	12-station base unit controller, expands to 54-stations, plastic pedestal
ACC-PED	Metal pedestal, gray powder-coated, for use with A2C-1200-M
PED-SS	Stainless steel pedestal for use with A2C-1200-SS

STATION EXPANSION MODULES	
Modules	Description
A2M-600	6-station plug-in module for use with the A2C-1200 series controllers
A2C-F3	3 input flow meter expansion module
A2C-WIFI	Internal Wi-Fi module

ACC2 DECODER

Number of Stations: **75 to 225**
Type: **Modular Decoder**

FEATURES

- Number of stations: 75 to 225
- Type: Modular Decoder
- Enclosure: Outdoor metal, stainless steel, plastic pedestal
- Full-color, high-resolution backlit display (reversible)
- Independent programs: 32
- Start times per program: 10
- Station run times: 15 seconds to 12 hours
- Optional Wi-Fi interface
- Real-time flow monitoring (up to 6 flow meters and flow zones)
- Up to 6 Pump/Master Valve outputs, Normally Open or Normally Closed
- Flow Management (runs flow zones to specified capacity)
- Monthly flow budgeting
- Built-in Solar Sync® logic/Solar Sync Delay feature
- SD card updates and log storage
- 12 selectable languages

► = *Advanced Feature descriptions on page 88*

DECODER FEATURES

- Operates all Hunter ICD decoders
- Three two-wire paths per output module
Up to 10,000 ft/3 km on 14 AWG/2 mm² wire
Up to 15,000 ft/4.5 km on 12 AWG/3.3mm² wire
- Replaceable automotive fuses included in each output module
- P/MV and flow sensor assignments either locally or via two-wire path
- Decoder inventory and update via two-wire path
- Decoder/solenoid finder
- Wire test mode for field diagnostics
- ICD-HP wireless programmer compatible

ELECTRICAL SPECIFICATIONS

- Transformer input: 120/230 VAC, 50/60 Hz
- Max AC current draw: 120 VAC, 2 A/230 VAC, 1 A
- Transformer output: 24 VAC, 4 A
- P/MV outputs (24 VAC): Up to 6; 3 dedicated outputs with optional assignment to decoders.
- Simultaneous program operation: Up to 20
- Sensor inputs: 3 Klik, 1 Solar Sync, and 6 Flow sensors

APPROVALS

- CE, UL, c-UL, RCM, FCC

ENCLOSURE RATING

- Metal wall mount (includes stainless): IP44
- Plastic pedestal: IP24

ACC2 DECODERS	
Model	Description
A2C-75D-M	75-station base model, gray metal outdoor, wall mount
A2C-75D-SS	75-station base model, stainless steel, wall mount
A2C-75D-PP	75-station base model, plastic pedestal
A2C-D75	75-station decoder expansion module
A2C-F3	Optional Flow Meter expansion module (adds 3 inputs)
ACC-PED	Gray pedestal for wall mount
PED-SS	316 stainless steel pedestal for wall mount



Metal Wall Mount (gray or stainless)

Height: 15.7"
Width: 15.7"
Depth: 6.8"



A2C-D75 Expansion Module

Expand any ACC2 Decoder controller in 75-station increments, up to 225 stations.



ICD-100, 200,

ICD-SEN
Height: 3½"
Width: 1½"
Depth: ¾"

ICD-400, 600

Height: 3½"
Width: 1¾"
Depth: 1½"

DECODER MODULES

Model	Description
ICD-100	Single-station decoder with surge suppression
ICD-200	2-station decoder with surge suppression
ICD-400	4-station decoder with surge suppression
ICD-600	6-station decoder with surge suppression
ICD-SEN	Sensor decoder with surge suppression

ACC 2 SERIES STATION EXPANSION

Model	Description
A2C-D75	75-station decoder expansion module