

ACCU-SYNC®

Type: **Pressure Regulator**

OPERATING SPECIFICATIONS

- Regulation from 20 to 100 PSI
- Static pressure: 150 PSI
- Required dynamic pressure differential: 15 PSI
- Works with AC and DC latching solenoids
- Works with any Hunter valve

ACCU-SYNC VALVE RECOMMENDED FLOW RANGE

Valve	Flow GPM
PGV-100/101	5 to 40
PGV-151	20 to 120
PGV-201	40 to 150
ICV-101	5 to 40
ICV-151	20 to 150
ICV-201	40 to 200
ICV-301	150 to 300
IBV-101	5 to 40
IBV-151	20 to 150
IBV-201	40 to 200
IBV-301	150 to 300

ACCU-SYNC APPLICATIONS

● Adjustable 20-100 PSI	For full customization, the adjustable Accu-Sync can regulate pressure from 20 to 100 PSI
● Fixed 30 PSI	Ideal for spray systems
● Fixed 40 PSI	Ideal for Hunter's MP Rotator and large in-line drip systems
● Fixed 50 PSI	Ideal for mid-range rotors
● Fixed 70 PSI	Ideal for larger rotors

ADJUSTABLE



AS-ADJ
Height with solenoid: 3¼"

ADAPTER



SOLENOID ADAPTER

FIXED



AS-30
Height with solenoid: 3¼"



AS-40
Height with solenoid: 3¼"



AS-50
Height with solenoid: 3¼"



AS-70
Height with solenoid: 3¼"



Installation

Accu-Sync shown installed on ICV and PGV valves.