




BUBBLER NOZZLES

FEATURES

- Pressure compensation ensures uniform output across various pressures
- Provides the correct amount of water, reducing runoff or waste
- Nozzle threaded for use with Pro-Spray®

MULTI-STREAM BUBBLER PERFORMANCE DATA

Arc	Model	Flow GPM	Radius ft.
	MSBN-25Q	0.25	1.0
	MSBN-50Q	0.50	1.5
	MSBN-50H	0.50	1.0
	MSBN-10H	1.00	1.5
	MSBN-10F	1.00	1.0
	MSBN-20F	2.00	1.5

Notes:

Typical spacing 2 to 4 ft. Flows shown for pressures between 15 and 70 PSI.

Multi-Stream Bubbler



MULTI-STREAM BUBBLER NOZZLES



MSBN-25Q
Flow: 0.25 GPM



MSBN-50Q/50H
Flow: 0.50 GPM




MSBN-10H/10F
Flow: 1.0 GPM



MSBN-20F
Flow: 2.0 GPM

PCN PERFORMANCE DATA

	Model	Flow GPM	Pattern Type
	25	0.25	Trickle
	50	0.50	Trickle
	10	1.00	Umbrella
	20	2.00	Umbrella

Notes:

Typical spacing 2 to 4 ft. Flows shown for pressures between 15 and 70 PSI.

PCN



PCN BUBBLER NOZZLES



PCN-25
Flow: 0.25 GPM



PCN-50
Flow: 0.50 GPM



PCN-10
Flow: 1.0 GPM



PCN-20
Flow: 2.0 GPM



MSBN Installed on PROS-04

Combining Hunter Bubbler Nozzles with the Pro-Spray provides the watering precision of pressure compensating bubblers paired with the benefit of retracting the nozzle out of sight.